

COUNTY	ROOSEVELT		FIELD	Chaveroo	STATE	NM
OPR	PAN AMERICAN PETROLEUM CORP.				MAP	
	13 Farrell, J. F. USA					
	Sec. 28, T-7-S, R-33-E				CO-ORD	
	660' FNL, 660' FWL of Sec.					
	Spd 1-31-66		CLASS		EL	
	Cmp 2-11-66		FORMATION	DATUM	FORMATION	DATUM
CSG & SX - TUBING						
	8 5/8"	417'	250			
	4 1/2"	4448'	800			
LOGS EL GR RA IND HC A						
			TD 4448', PRD 4414'			

IP San Andres Perfs 4246-4388' Pmpd 83 BOPD + 2 BW. Pot. Based on 24 hr test, gravity 24., GOR 752.

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT.	PROP DEPTH	4500'	TYPE
DATE			

F.R. 1-27-66; Opr's Elev. 4425' KB
 PD 4500' - SA
 2-7-66 Drlg. 4320'.
 2-14-66 TD 4448', PRD 4414', swbg load.
 Perf 4246-47', 4249-51', 4253-54', 4262-66', 4273-74', 4282-84', 4285-86', 4290-91', 4298-99', 4301-02', 4308-10', 4314-15', 4317-18', 4322-25', 4372-74', 4380-81', 4383-84', 4386-88' W/2 SPF
 Ac (4246-4388') 2000 gals; IR 4 BPM
 Swbd 24 BLW + 1 BO/7½ hrs.
 Frac (4246-4388') 30,000 gals oil + 30,000# sd. + 3,000# glass beads
 IR 33.1 BPM
 Swbd 63 BLW + 2 BO/4 hrs.

2-21-66 TD 4448', PBD 4414', pmpg load.
Pmpd 128 BLO + 4 BW/30 hrs.
2-28-66 TD 4448', PBD 4414', COMPLETED.
Pmpd 75 BLO, 10 BNO + 4 BW/24 hrs.
LOG TOP: San Andres 3440'.