

50-041-10759

COUNTY	ROOSEVELT		FIELD	Chaveroo		STATE	NM	
OPR	CHAMPLIN PETROLEUM COMPANY						MAP	
	7 Lauck-Federal							
	Sec. 29, T-7-S, R-33-E						CO-ORD	
	1980' ENL, 1980' FWL of Sec.							
	Spd 1-22-66		CLASS		EL			
	Cmp 2-9-66		FORMATION	DATUM	FORMATION	DATUM		
CSG & SX - TUBING								
8 5/8" 380' 225								
4 1/2" 4429' 325								
LOGS EL GR RA IND HC A								
			TD 4430'					

IP San Andres Perfs 4182-4387' Swbd 176 BOPD + 44 BW. Pot.
Based on 24 hr test, gravity 24.6.

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. Sitton & Norton	PROP DEPTH	4500'	TYPE
DATE			

F.R. 1-27-66
PD 4500' - SA
Contractor - Sitton & Norton

2-1-66 Drlg. 4193'.
Set 8 5/8" @ 380' W/225 sx.

2-7-66 TD 4430', WOC.
Cored 4379-4430', rec 51' lm & dolo.,
w/scatt shows oil & gas.
Set 4 1/2" @ 4429' W/325 sx.

2-14-66 TD 4430', prep to RU Pump.
Perf @ 4182', 4210', 4238', 4248', 4266',
4277', 4294', 4325', 4376', 4387'
Ac (4182-4387') 2500 gals
Frac (4182-4387') 40,000 gals wtr +
40,000# sd.
Swbd 220 BF (80% oil) in 24 hrs.

ROOSEVELT Chaveroo NM Sec. 29-7S-33E
CHAMPLIN PETROLEUM CO., #7 Lauck-Federal Page #2

2-21-66

TD 4430', COMPLETED.

LOG TOPS: Anhydrite 1845', Yates 2288',
Queen 2971', San Andres 3524'.