16.

UN CD STATES SUBMIT IN TRIPIDEPARTME... OF THE INTERIOR (Other Instruction: verse side) UN "ED STATES

Budget Bureau No. 42-R1424. 5. LEASE DESIGNATION AND SERIAL NO.

25

GEO	OCICAL	SHRVEY

GEOLOGICAL SURVEY	Federal NM-0554778
SUNDRY NOTICES AND REPORTS ON WELLS	6. JF INDIAN, ALLOTTEE OR TRIBE NAM
this form for proposals to drill or to deepen or plug back to a different reservoir.	

(Do not use this form for prop Use "APPLI	osals to drill or to deepen or plug back to a different reservoir. CATION FOR PERMIT—" for such proposals.)		
OIL X GAS OTHER	7. UNIT AGREEMENT NAME		
2. NAME OF OPERATOR Champlin Petroleum	8. FARM OR LEASE NAME Lauck-Federal		
3. ADDRESS OF OPERATOR 701 Wilco Bldg., Mi	dland, Texas 79701	9, WELL NO.	
 LOCATION OF WELL (Report location See also space 17 below.) At surface 	10. FIELD AND POOL, OR WILDCAT Chaveroo-San Andres		
660' FNL & 660' FWI State Unit "D"	, Section 29, T-7-S, R-33-E,	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 29, T-7-S, R-33-E	
14. FERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.)	12. COUNTY OR PARISH 13. STATE	
	4403 GR	Roosevelt New Mexico	

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOT	ICE OF INT	ENTION TO:	SUE	SEQUENT REPORT	r or:	
TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL (Other)		PULL OR ALTER CASING MULTIPLE COMPLETE ABANDON* CHANGE PLANS	WATER SHUT-OFF FRACTURE TREATMENT SHOOTING OR ACIDIZING (Other) (NOTE: Report res Completion or Reco	sults of multiple	REPAIRING WELL ALTERING CASING ABANDONMENT* completion on Wel	X
			 Completion of Reco	ompletion Repor	t and Log form.)	

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

Well was plugged and abandoned as follows:

- Set cast iron bridge plug at 4200'. Dumped 35' cement to 4165'.
- 3/19/73 2. Recovered 616' 4½" casing.
 - Set 35 sk. cement plug inside $4\frac{1}{2}$ " casing 1800-2318.
 - Set 35 sk. cement plug 380-248'.
 - Set 10 sk. cement plug at surface and installed dry hole marker.

Well circulated with, and all cement plugs set with, salt water gel mud.

·			actors togeths, or to account of the program of the
18. I hereby certify that the foregoing is true and correct			
SIGNED West M. Rendered	TITLE	District Clerk	DATE April 4, 1973
(This space for Federal or State office use)		APPROV	35,00 34 125
APPROVED BY	TITLE	1	IN PARE
CONDITIONS OF APPROVAL, IF ANY:		OCT 24 191	
* \$	ee Instructions	OCT 24 150	NEBY AND STATE
		1 (2)(3)(1)	