

COUNTY	ROOSEVELT		FIELD	Chaveroo	STATE	NM
OPR	CHAMPLIN PETROLEUM COMPANY				MAP	
	8 State					
	Sec. 32, T-7-S, R-33-E				CO-ORD	
	1980' FSL, 1980' FWL of Sec				MX 10443	
	Spd 2-28-66		CLASS	EL [REDACTED]		
	Cmp 3-18-66	FORMATION	DATUM	FORMATION	DATUM	
CSG & SX - TUBING						
8 5/8" 376' 275						
4 1/2" 4490' 325						
LOGS EL GR RA IND HC A						
	TD 4490', PBD 4488'					

IP San Andres Perfs 4214-4428' Swbd 142 BOPD + 213 BW. Pot.
Based on 24 hr test, gravity 24.6, GOR 120.

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. Sitton & Norton PROP DEPTH 4500' TYPE
DATE

F.R. 2-10-66
PD 4500' - SA
Contractor - Sitton & Norton
3-7-66 Drlg. 4133'.
3-14-66 TD 4490', WOC.
3-21-66 TD 4490', PBD 4488', rec'g load.
Perf @ 4214', 4224', 4236', 4246', 4252',
4269', 4292', 4304', 4311', 4324', 4331',
4342', 4373', 4420', 4428'
Ac (4214-4428') 2500 gals.
Frac (4214-4428') 50,000 gals wtr +
40,000# sd.
3-28-66 TD 4490', PBD 4488', pmpg load.
Pmpd 135 BLW/24 hrs.
4-4-66 TD 4490', PBD 4488', COMPLETED.
LOG TOPS: Yates 2322', Queen 3000',
San Andres 3568'.