

Form 9-331
(May 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
FEB 0 11 12 AM '66
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 0108997 (A)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

San American Petroleum Corp.

3. ADDRESS OF OPERATOR

Box 68 Hobbs, New Mexico

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1980 FNL x 1980 FWL, Sec. 28 (Unit F SE 1/4 NW 1/4)

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4426' R.D.B.

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

J.F. FARRELL-USA

9. WELL NO.

10

10. FIELD AND POOL, OR WILDCAT

CHAUEROO SAN ANDRES

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

28-7-33 NMPM

12. COUNTY OR PARISH

ROOSEVELT

13. STATE

NM

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

Completion Operations
(Note: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

On 1-26-66, 4 1/2" OD 9.5# J-55 casing was set at
4433' (TD-4455) w/ 500 sy Incor 12% Gel + 300 sy neat.
Tested casing w/ 2000 psi for 30 minutes. Test O.K.
Perforated intervals 4239-40, 45-47, 56-60, 62-64, 72-73, 77-79, 83-84,
85-86, 97-98, 4305-06, 12-13, 17-19, 25-26, 61-62, 67-68, 73-74, 76-78, 81-82, 87-88,
w/ 25 SPF. Acidized w/ 2000 gallons.

PT, Shredded 9 hours, 61 BO x 99 BW. Cgr. 25°
GOR, NA.

TD-4455

PBD-4396

PSA-4344

Comp. 2-3-66

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Area Supt

DATE

(This space for Federal or State office use)

0-4-5545-14

1-JWB

1-5032

1-R24

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

2-Champion Pils Co

1-Warren Amer Oil Co

1-Kern Co Land Co

3-Tom Brown Stry

*See Instructions on Reverse Side

APPROVED

FEB 7 1966

J. L. GORDON
ACTING DISTRICT ENGINEER