

COUNTY	ROOSEVELT		FIELD	Chaveroo		STATE	NM	
OPR	PAN AMERICAN PETROLEUM CORP.						MAP	
	12 Farrell, I. E. USA							
	Sec. 28, T-7-S, R-33-E						CO-ORD	
	1980' ENL, 1980' FEL of Sec.							
	Spd 1-26-66		CLASS		E [REDACTED]			
	Cmp 2-18-66		FORMATION	DATUM	FORMATION	DATUM		
CSG & SX - TUBING								
8 5/8" 412' 250								
4 1/2" 4454' 800								
LOGS EL GR RA IND HC A								
			TD 4454', PBD 4407'					

IP San Andres Perfs 4232-4365' Flwd 182 BOPD + 2 BW. Pot.
Based on 24 hr test thru 32/64" chk., TP 500#, CP 950#,
GOR 1628, gravity 25.

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT.	PROP DEPTH	4500'	TYPE
DATE			

F.R. 12-16-63
PD 4500' - SA
1-31-66 Drlg. 3462'.
Set 8 5/8" @ 412 W/250 sx.
2-7-66 TD 4454', prep to run casing.
Cored 4160-4210', rec 50' dolo., w/anhydritic
inclusions, PPP, bleeding oil & gas.
Cored 4210-4260', rec 50' dolo., w/vert
fracs., bldg oil & gas.
Cored 4260-4310', rec 50' same.
Cored 4310-4360', rec 50' same.
Cored 4360-4410', rec 50' same.
2-14-66 TD 4454', PBD 4407', tstg.
Set 4 1/2" @ 4454' W/800 sx.

2-14-66

Continued

Perf 4232-34', 4235-37', 4242-44', 4256-60',
4262-64', 4266-67', 4274-75', 4279-80',
4287-88', 4303-07', 4349-50', 4352-54',
4361-65' W/2 SPF

Ac (4232-4365') 2000 gals

IR 4.5 BPM @ 1900-1500#

Frac (4232-4365') 30,000 gals oil +
30,000# sd. + 3000# glass beads;

IR 37.2 BPM

Swbd 46 BLO + 5 BLW/5 hrs.

2-21-66

TD 4454', PBD 4407', COMPLETED.

On Pot. Flowed 219 BLO, 182 BNO + 2 BW
in 24 hrs thru 32/64" chk., TP 500#, CP
950#, GOR 1628, gravity 25.

LOG TOP: San Andres 3430'.