

COUNTY	ROOSEVELT		FIELD	Chaveroo	STATE	NM
OPR	CHAMPLIN PETROLEUM COMPANY				MAP	
	6 Lauck-Federal					
	Sec. 29, T-7-S, R-33-E				CO-ORD	
	1980' FNL, 1980' FEL of Sec.					
	Spd 1-12-66					
	Cmp 1-30-66					
	FORMATION		CLASS		EL	
	DATUM		FORMATION		DATUM	
CSG & SX - TUBING						
8 5/8" 370' 200						
4 1/2" 4425' 325						
LOGS EL GR RA IND HC A						
	TD 4425', PBD 4419'					

IP San Andres Perfs 4188-4392' Swbd 163 BOPD + 41 BW. Pot.
Based on 24 hr test.

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. Sitton & Norton	PROP DEPTH 4500'	TYPE
DATE		

F.R. 12-30-65
PD 4500' - SA
Contractor - Sitton & Norton
1-17-66 Drlg. 4040'.
Set 8 5/8" @ 370' W/200 sx.
1-24-66 TD 4425', PBD 4419', MI Completion Unit.
DST 4220-4425', open 1 hr 30 mins,
GTS in 1 hr 25 mins,
Rec 60' GCO, + 340' G&HO Cut Mud,
1 hr ISIP 1334#, FP 191-277#,
1 hr 30 min PSIP 1270#.
Set 4 1/2" @ 4425' W/325 sx.
2-1-66 TD 4425', PBD 4419', swbg.
Perf @ 4188', 4208', 4251', 4261', 4279',
4284', 4292', 4302', 4323', 4374', 4386',
4392' W/2 SPI

ROOSEVELT Chaveroo NM
CHAMPLIN PETROLEUM CO., #6 Lauck-Federal

Sec. 29-7S-33E
Page #2

-1-66 Continued
Ac (4188-4392') 2500 gals.
Frac (4188-4392') 40,000 gals wtr +
40,000# sd.
Swbd 163 BO + 41 BW/24 hrs.
2-7-66 TD 4425', PBD 4419', COMPLETED.
(Holding for tops)
2-21-66 TD 4425', PBD 4419', Completion Reported.
LOG TOPS: Anhydrite 1865', Yates 2299',
Queen 2971', San Andres 3523'.