

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION BOARD OFFICE O.C.C.

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

APR 26 9 AM '66

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. State - OG-1395	

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name NONE
2. Name of Operator TEXACO Inc.	8. Farm or Lease Name State N.M. "CT"
3. Address of Operator P. O. Box 728 - Hobbs, New Mexico	9. Well No. 2
4. Location of Well UNIT LETTER <u>H</u> <u>1980</u> FEET FROM THE <u>North</u> LINE AND <u>660</u> FEET FROM THE <u>East</u> LINE, SECTION <u>35</u> TOWNSHIP <u>7-S</u> RANGE <u>35-E</u> N.M.P.M.	10. Field and Pool, or Wildcat Todd San Andres
15. Elevation (Show whether DF, RT, GR, etc.) <u>4358' (GR)</u>	12. County Roosevelt

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Total Depth - 357'
Spudded 9 7/8" Hole at 6:00 A. M. April 22, 1966

Ran 346' of 7 5/8" O. D. Casing, 15.28 LB, Spiral Weld, NEW, and cemented at 357' with 200 Sx. Incor Class "C" cement. Plug at 327'. Cement Circulated.

Temperature of mixing slurry - 75°, - 12 Hour Strength - 1000 P. S. I.
Bottom Hole Temperature - 74°, - Job complete 7:00 P. M. April 22, 1966.

Tested 7 5/8" O. D. Casing for 30 minutes with 600 P. S. I. from 1:00 A. M. to 1:30 A. M. April 23, 1966. Tested O. K. Drilled cement plug and re-tested for 30 minutes with 600 P. S. I. from 2:00 A. M. to 2:30 A. M. April 23, 1966. Tested O. K. Job complete 2:30 A. M. April 23, 1966.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Dan Gillett TITLE Assistant District Superintendent DATE April 26, 1966

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY: