

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

RECEIVED OFFICE O. C. C.
MAR 30 3 07 PM '66

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. E - 1369
7. Unit Agreement Name -
8. Farm or Lease Name Hobbs "T" T. B. #2
9. Well No. 15
10. Field and Pool, or Wildcat Chavez San Andres
12. County Reynolds

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>
2. Name of Operator Shelly Oil Company
3. Address of Operator Box 730 - Hobbs, New Mexico
4. Location of Well UNIT LETTER "Q" 990 FEET FROM THE South LINE AND 1900 FEET FROM THE East LINE, SECTION 24 TOWNSHIP 7S RANGE 33E NMPM.
15. Elevation (Show whether DF, RT, GR, etc.) 4397' RT

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
FULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Reached total depth of 4500' at 4:30 p.m., March 23, 1966. Set 139 jts (4478') of 4-1/2" OD 10.5# DR 25 J-55 RT & C casing at 4490'. Cemented with 350 sacks of cement by the pump & plug process. Plug down at 9:30 a.m., March 25, 1966. Temperature survey indicated cement behind 4-1/2" OD casing at 3309' from the surface, W.O.C 24 hrs. Pressured casing up to 600# for 30 minutes and casing tested OK. Did not drill out cement plug. P.B.T.D. 4450'.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED **(ORIGINAL SIGNED) H. E. Aab** TITLE **District Superintendent** DATE **March 30, 1966**
APPROVED BY _____ TITLE **Engineer** DATE _____
CONDITIONS OF APPROVAL, IF ANY: