

COUNTY	ROOSEVELT		FIELD	Wildcat		STATE	NM	
OPR	THE WIL-Mc OIL CORPORATION						MAP	
	1 Baker							
	Sec. 9, T-8-S, R-35-E						CO-ORD	
	1980' ENL, 660' EWL of Sec.						MX 10481	
	Std 3-12-66						EL	
	Cmp 6-3-66		CLASS				EL	
			FORMATION	DATUM	FORMATION	DATUM		
CSG & SX - TUBING								
	8 5/8"	372'	275					
	4 1/2"	4719'	200					
LOGS EL GR RA IND HC A								
			TD 4720'					
PLUGGED & ABANDONED								

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. Verna Drilg. Co.	PROP DEPTH	4800'	TYPE
DATE			

E.S. 3-17-66
 FD 4800' - SA
 Contractor - Verna Drilg. Co.
 3-21-66 Drilg. 4486'
 3-28-66 TD 4720', WOC.
 DST 4667-4720', open 1 hr 20 mins,
 Rec 30' gas in DP + 60' GOM,
 1 hr ISIP 1492#, FP 46-69#,
 2 hr FSIP 1469#.
 4-4-66 TD 4720', PSD 4650', swbg.
 Perf @ 4671', 4685', 4693', 4700', 4704'.
 Ac (4671-4704') 2000 gals.
 Swbd acid wtr & salt wtr (4671-4704')
 Set BP @ 4650'
 Perf @ 4621', 4633', 4636', 4641'
 Ac (4621-41') 1000 gals.

4-4-66 Continued
Swbg 2-3 BAW & Salt Wtr PH, w/sli show
of oil & gas.

4-11-66 TD 4720', PBD 4650', swbg load.
Frac (4621-41') 15,000 gals oil +
15,000# sd.
Swbd 110 BLO/8 hrs.

4-18-66 TD 4720', PBD 4650', RU Pump.
Swbd 50 BLO + 50 BW/10 hrs.

4-25-66 TD 4720', PBD 4650', SD Pump Repairs.
Pmpd 52 B Salt Wtr in 20 hrs.

5-2-66 TD 4720', PBD 4650', tstg on pump
(no gauge)

5-9-66 TD 4720', PBD 4650', pmpg load.
Pmpd 8 BLO + 35 BW/24 hrs.

5-16-66 TD 4720', PBD 4650', pmpg load.

5-23-66 TD 4720', PBD 4650', pmpg load.

5-31-66 TD 4720', PBD 4650', prep to P&A.
Did not rec load from perfs 4621-41'
(-58 BLO)

6-6-66 TD 4720', PBD 4650', PLUGGED & ABANDONED.
LOG TOPS: Anhydrite 2158', Yates 2697',
San Andres 3880', Slaughter 4655'.