

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

HOBBS OFFICE D. G. B.
 NEW MEXICO OIL CONSERVATION COMMISSION
 MAY 4 1 05 PM '66

Form C-103
 Supersedes Old
 C-102 and C-103
 Effective 1-1-65

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. E-9956
7. Unit Agreement Name
8. Farm or Lease Name State B
9. Well No. 1
10. Field and Pool, or Wildcat Undesignated (Wildcat)
12. County Roosevelt

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- dry hole
2. Name of Operator FRANKLIN, ASTON & FAIR, INC.
3. Address of Operator P. O. Box 1090, Roswell, New Mexico
4. Location of Well UNIT LETTER B 660 FEET FROM THE North LINE AND 1980 FEET FROM THE East LINE, SECTION 17 TOWNSHIP 7S RANGE 33E NMPM.
15. Elevation (Show whether DF, RT, GR, etc.) 4412' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Pursuant to telephone conversation with Mr. Engbrecht on May 3, 1966, we plan to plug and abandon this well as follows:

Spot 15 sacks cement across perforations at 4116'-4232' with tubing. We will then run free point and shoot casing and spot 25 sacks cement where casing is shot. We will then spot 25-sack plug at the base of the salt at 1900', 25-sack plug at the top of the salt at 750', 25-sack plug across bottom of the 8 5/8" surface casing at 355', and 10-sack plug with marker at surface.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>Grant M. Smith</u>	TITLE <u>Geologist</u>	DATE <u>May 3, 1966</u>
APPROVED BY _____	TITLE _____	DATE _____
CONDITIONS OF APPROVAL, IF ANY:		