State B Some of Operator P. O. BOX 1090, ROSWELL, NEW MEXICO Cocretion of Well MILLETER B LOCATED G60 FEET FROM THE MORTH 1980 FEET FROM THE MORTH 1980 FEET FROM THE MORTH ROSSEVEIT Liver of Mort 1980 FEET FROM THE MORTH 1980 FEET FROM THE MORTH ROSSEVEIT 1980 FEET FROM THE MORTH 1980 FEET FROM THE MORTH 1980 FEET FROM THE MORTH 1981 FEET FROM THE MORTH 1982 FEET FROM THE MORTH 1983 FEET FROM THE MORTH 1984 FEET FROM THE MORTH ROSSEVEIT ROSSEVEIT 1984 FEET FROM THE MORTH 1984 FEET FROM THE MORTH 1984 FEET FROM THE MORTH ROSSEVEIT ROSSEVEIT 1984 FEET FROM THE MORTH ROSSEVEIT ROSSEVEIT 1984 FEET FROM THE MORTH 1984 FEET FROM THE MORTH 1984 FEET FROM THE MORTH ROSSEVEIT ROSSEVEIT ROSSEVEIT ROSSEVEIT ROSSEVEIT ROSSEVEIT 1984 FEET FROM THE MORTH ROSSEVEIT 1984 FEET FROM THE MORTH ROSSEVEIT ROSSEVE	NOTATE LE S.O.3. NO OFFICE SENATOR APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK Type of Work PLUG BACK Type of Work Type of			NEW!	MEXICO OIL CONSI	TONE TION COMM			
APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK Same Oil 6 Cas Lease No. 6-9956	### 21 State of Lesson State Type of Lesson State Type of Lesson State Type of Wark ### APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK State State				,,_,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	ERVATION COMMI	SSION HUBB?	Pevised 1-1-6	9, 19,
S.G.3. NO OFFICE PERATOR APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK Type of Work Typ	S.G.3. INDOOPTICE SERATOR APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK Type of Work APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK Type of Work DRILL						W = 21		
Secretary of Work APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK Type of Well APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK Type of Well APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK Type of Well APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK Type of Well APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK Type of Well APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK Type of Well APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK Type of Well APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK Type of Well APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK Type of Well APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK Type of Well APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK To Plug Back Type of Well APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK To Plug Back To Plug Back The Plug Back T	SPENDED FRICE SPENDED FROM CIT & CORE Lender NO. E-9956 APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK Type of Work DRILL D D						MAR ZI	11.3	
APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK Type of Work DRILL A DEEPEN DEEPEN DIVISION OF PLUG BACK Type of Work PLUG BACK State 8 State 9 S	APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK Type of West Type of West DRILL							L	
APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK Type of Work DRILL	APPLICATION FOR PERMIT TO DRILL_DEEPEN, OR PLUG BACK Type of Well Type		 					1 .	
Type of Wall Type of Wall Type of Wall Type of Wall Acc. Other Other O	Type of Well Type of Type of Well Type of Well Type of Well Type of Well Type of	*						WIIII	
Type of Wall Ty	Type of Well Ty	APPLICATIO	N FOR PER	RMIT TO	DRILL, DEEPEN	OR PLUG BACK	ζ		
Type of Well State 8 State 8	Type of Well State State							7. Unit Agre	ement Name
Type of Well State 8 State 8	Type of Well State State	DBII 1	7		DEEDEN	p	LUG BACK		
WELL CATE OF THE TONE TONE TONE TONE TONE TONE TONE TON	TRANKLIN, ASTON & FAIR, INC. 1	Type of Well	Y		DEEFEN			8. Form or L	ease Name
FRANKLIN, ASTON & FAIR, INC. 10. PED and POOL or Wilders 10. PED and POO	FRANKLIN, ASTON & FAIR, INC. 10, Field and Peol, or Wilders 12, County 12, County		OTHE	R					8
10, Field and Fool, or Wulfert 10, Field and Fool, or C.T. And Fool, or C.	Undest gnated 10. Field end Pool, or Willerst 10. Market 1	Name of Operator						9. Well No.	
P. O. BOX 1090, ROSWELL, NEW MEXICO 1980 PROPERTY FOR THE B LOCATED 660 FEET FROM THE NORTH LINE 1980 PROPERTY FOR THE 1980	P. O. BOX 1090, ROSWELL, NEW MEXICO DITLETER B LOCATED 660 FEET FROM THE NORTH LINE 1980 FEET FROM THE NORTH LINE 19. PROPOSED DEPTH 19. PROPOSED LINE OF CASING WEIGHT PER POOL SETTING DEPTH SACKS OF CEMENT EST. TOP 12. Approx. Date Work will elect the set of my knowledge and belief. Plan to drill 12 3/4" hole to 250' and run 8 5/8" 24# J-55 Casing and set with 250 sacks cement 2% CaCl; let set 12 hours. Pressure up to 800 psi, hold 15 minutes, then drill 7 7/8" hole to 4600' and log. If logs indicate formation to be productive, we will run 4 1/2" 9.5# casing to TD and set with 250 sacks cement 2% CaCl per sack and attempt completion.	FRANKLIN, ASTON &	FAIR, IN	<u> 1C.</u>				1 1	,
1980 PEET FROM THE East LINE OF BEC. 17 TWP. 75 Rage. 33E MMPN 12. Country Roosevelt	1980 PROPOSED CASING AND CEMENT PROGRAM SIZE OF HOLE SIZE OF CASING WEIGHT PER FOOT SETTING DEPTH SACKS OF CEMENT SACKS OF	•							
1980 FEET FROM THE EBST LINE OF SEC. 17 FWP. 75 REE. 33E NAME ROOSEVELT RESIDENCE TO THE FOREST PROPERTY OF SEC. 17 FWP. 75 REE. 33E NAME ROOSEVELT ROOSEVEL	1980 ***PECT FROM THE East LINE OF SEC. 17 TWP. 75 not. 33E NAMED AND THE EAST LINE OF SEC. 17 TWP. 75 NOT. 33E NAMED AND THE EAST LINE OF SEC. 17 TWP. 75 NOT. 33E NAMED AND THE EAST LINE OF SEC. 17 TWP. 75 NOT. 33E NAMED AND THE EAST LINE OF SEC. 17 TWP. 75 NOT. 33E NAMED AND THE EAST LINE OF SEC. 17 TWP. 75 NOT. 33E NAMED AND THE EAST LINE OF SEC. 17 TWP. 75 NAMED AND THE EAST LINE OF SEC. 17 TWP. 75 NAMED AND THE EAST LINE OF SEC. 17 TWP. 75 NAMED AND THE EAST LINE OF SEC. 17 TWP. 75 NAMED AND THE EAST LINE OF SEC. 17 TWP. 75 NAMED AND THE EAST LINE OF SEC. 17 TWP. 75 NAMED AND THE EAST LINE OF SEC. 17 TWP. 75 NAMED AND THE EAST LINE OF SEC. 17 TWP. 75 NAMED AND THE EAST LINE OF SEC. 17 TWP. 75 NAMED AND THE EAST LINE OF SEC. 17 TWP. 75 NAMED AND THE EAST LINE OF SEC. 17 TWP. 75 NAMED AND THE EAST LINE OF SEC. 17 TWP. 75 NAMED AND THE EAST LINE OF SEC. 17 TWP. 75 NAMED AND THE EAST LINE OF SEC. 17 TWP. 75 NAMED AND THE EAST LINE OF SEC. 17 TWP. 75 NAMED AND THE EAST LINE OF SEC. 17 TWP.		ROSWELL, N	NEW MEX				Undesi	gnated Fill (4)
PROPOSED CASING AND CEMENT PROGRAM SIZE OF HOLE SIZE OF CASING PROPOSED CASING WEIGHT PER FOOT 12 3/4" 8 5/8" 2 14 1/2" 9 5# 4600' Plan to drill 12 3/4" hole to 250' and run 8 5/8" 24# J-55 Casing and set with 250 sacks cement 2% CaCl; let set 12 hours. Pressure up to 800 psi, hold 15 minutes, then drill 7 7/8" hole to 4600' and log. If logs indicate formation to be productive, we will run 4 1/2" 9.5# casing to TD and set with 250 sacks cement 2% CaCl per sack and attempt completion.	Plan to drill 12 3/4" hole to 250' and run 8 5/8" 250 1 150 Circulate 7 7/8" 4 1/2" 9.5# 4600' 250 3600' Plan to drill 12 3/4" hole to 250' and run 8 5/8" 250 1 150 Circulate 7 7/8" 4 1/2" 9.5# 4600' 250 3600' Plan to drill 17 7/8" hole to 250' and run 8 5/8" 250 1 150 Circulate 7 7/8" 4 1/2" 9.5# 4600' 250 3600' Plan to drill 17 7/8" hole to 250' and run 8 5/8" 250 1 150 Circulate 7 7/8" 4 1/2" 9.5# 4600' 250 3600' Plan to drill 17 7/8" hole to 250' and run 8 5/8" 250 1 150 Circulate 7 7/8" 4 1/2" 9.5# 4600' 250 3600' Plan to drill 17 7/8" hole to 250' and run 8 5/8" 250 1 150 Circulate 7 7/8" 4 1/2" 9.5# 4600' 250 3600' Plan to drill 17 7/8" hole to 4600' and log. If logs indicate formation to be productive, we will run 4 1/2" 9.5# casing to TD and set with 250 sacks cement 2% Gel 8# CaCl per sack and attempt completion.	Location of well unit LETT	ER 8	LOCA	ATED	FEET FROM THE NO	rth LINE		
PROPOSED CASING AND CEMENT PROGRAM SIZE OF HOLE SIZE OF CASING PROPOSED CASING WEIGHT PER FOOT 12 3/4" 8 5/8" 2 14 1/2" 9 5# 4600' Plan to drill 12 3/4" hole to 250' and run 8 5/8" 24# J-55 Casing and set with 250 sacks cement 2% CaCl; let set 12 hours. Pressure up to 800 psi, hold 15 minutes, then drill 7 7/8" hole to 4600' and log. If logs indicate formation to be productive, we will run 4 1/2" 9.5# casing to TD and set with 250 sacks cement 2% CaCl per sack and attempt completion.	Plan to drill 12 3/4" hole to 250' and run 8 5/8" 250 1 150 Circulate 7 7/8" 4 1/2" 9.5# 4600' 250 3600' Plan to drill 12 3/4" hole to 250' and run 8 5/8" 250 1 150 Circulate 7 7/8" 4 1/2" 9.5# 4600' 250 3600' Plan to drill 17 7/8" hole to 250' and run 8 5/8" 250 1 150 Circulate 7 7/8" 4 1/2" 9.5# 4600' 250 3600' Plan to drill 17 7/8" hole to 250' and run 8 5/8" 250 1 150 Circulate 7 7/8" 4 1/2" 9.5# 4600' 250 3600' Plan to drill 17 7/8" hole to 250' and run 8 5/8" 250 1 150 Circulate 7 7/8" 4 1/2" 9.5# 4600' 250 3600' Plan to drill 17 7/8" hole to 250' and run 8 5/8" 250 1 150 Circulate 7 7/8" 4 1/2" 9.5# 4600' 250 3600' Plan to drill 17 7/8" hole to 4600' and log. If logs indicate formation to be productive, we will run 4 1/2" 9.5# casing to TD and set with 250 sacks cement 2% Gel 8# CaCl per sack and attempt completion.	1090	Enet		17	70	225		
PROPOSED CASING AND CEMENT PROGRAM SIZE OF HOLE SIZE OF CASING WEIGHT PER FOOT 12 3/4" 8 5/8" 24# 12" Plan to drill 12 3/4" hole to 250' and run 8 5/8" 250 sacks cement 2% CaCl; let set 12 hours. Pressure up to 800 psi, hold 15 minutes, then drill 7 7/8" hole to 4600' and run 8 5/8" Plan to drill 17 7/8" hole to 250' and run 8 5/8" 250 sacks cement 2% CaCl; let set 12 hours. Pressure up to 800 psi, hold 15 minutes, then drill 7 7/8" hole to 4600' and log. If logs indicate formation to be productive, we will run 4 1/2" 9.5# casing to TD and set with 250 sacks cement 2% CaCl per sack and attempt completion.	Size of Hole Size of Casing Weight Per Pool Setting Depth Sacks of Cement Size of Hole Size of Casing Size of Casing Size of Hole Size of Casing Size of C	D 1900 FEET FROM	THE ESS	TTTTT	S OF SEC.	TWP. RGE.	TITITITI		<i>…\\\\\</i>
19. Proposed Depth 19A. Formation 20. Rotary or C.T. 4600' San Andres Rotary	19. Proposed Depth 19A. Formation 20. Rotary or C.T. 4600' San Andres Rotary							N	14 (((((()))))
Elevations (Show whether DF, RT, etc.) 21A. Kind 6 Status Plug. Bond 21B. Drilling Contractor Horan Drilling Company March 23, 1966 PROPOSED CASING AND CEMENT PROGRAM SIZE OF HOLE SIZE OF CASING WEIGHT PER FOOT 12 3/4" 8 5/8" 24# 250! 150 Circulate 7 7/8" 4 1/2" 9.5# 4600' Plan to drill 12 3/4" hole to 250' and run 8 5/8" 24# J-55 Casing and set with 250 sacks cement 2% CaCi; let set 12 hours. Pressure up to 800 psi, hold 15 minutes, then drill 7 7/8" hole to 4600' and log. If logs indicate formation to be productive, we will run 4 1/2" 9.5# casing to TD and set with 250 sacks cement 2% Gel 8# CaCl per sack and attempt completion.	Lievations (Show whether DF, RT; etc.) 21A. Kind & Status Plug. Bond 4412' GR PROPOSED CASING AND CEMENT PROGRAM SIZE OF HOLE SIZE OF CASING WEIGHT PER FOOT SETTING DEPTH SACKS OF CEMENT EST. TOP 12 3/4" 8 5/8" 214# 250! 150 Circulate 7 7/8" 4 1/2" 9.5# 4600' ACKS OF CEMENT EST. TOP 12 3/4" 8 5/8" 24# 250! 150 Circulate 7 7/8" 4 1/2" 9.5# 4600' Plan to drill 12 3/4" hole to 250' and run 8 5/8" 24# J-55 Casing and set with 250 sacks cement 2% CaCl; let set 12 hours. Pressure up to 800 psi, hold 15 minutes, then drill 7 7/8" hole to 4600' and log. If logs indicate formation to be productive, we will run 4 1/2" 9.5# casing to TD and set with 250 sacks cement 2% GaCl per sack and attempt completion.	HHHHHHH	++++++	/////	/////////////////////////////////////	/////////////////////////////////////	HHHHH	Titith	HHHhii
Elevations (Show whether DF, RT, etc.) 21A. Kind 6 Status Plug. Bond 21B. Drilling Contractor 4412' GR PROPOSED CASING AND CEMENT PROGRAM SIZE OF HOLE SIZE OF CASING WEIGHT PER FOOT 12 3/4" 8 5/8" 214# 250! 150 Circulate 7 7/8" 4 1/2" 9.5# 4600' Plan to drill 12 3/4" hole to 250' and run 8 5/8" 24# J-55 Casing and set with 250 sacks cement 2% CaCi; let set 12 hours. Pressure up to 800 psi, hold 15 minutes, then drill 7 7/8" hole to 4600' and log. If logs indicate formation to be productive, we will run 4 1/2" 9.5# casing to TD and set with 250 sacks cement 2% Gel 8# CaCl per sack and attempt completion.	Lievations (Show whether DF, RT, etc.) 21A. Kind & Status Plug. Bond 4412' GR PROPOSED CASING AND CEMENT PROGRAM SIZE OF HOLE SIZE OF CASING WEIGHT PER FOOT SETTING DEPTH SACKS OF CEMENT EST. TOP 12 3/4" 8 5/8" 214# 250! 150 Circulate 7 7/8" Plan to drill 12 3/4" hole to 250' and run 8 5/8" 24# J-55 Casing and set with 250 sacks cement 2% CaCl; let set 12 hours. Pressure up to 800 psi, hold 15 minutes, then drill 7 7/8" hole to 4600' and log. If logs indicate formation to be productive, we will run 4 1/2" 9.5# casing to TD and set with 250 sacks cement 2% Gel 8# CaCl per sack and attempt completion.								
SIZE OF HOLE SIZE OF CASING WEIGHT PER FOOT SETTING DEPTH SACKS OF CEMENT ST. TOP	### 21A. Kind & Status Plug. Bond Blanket Bond Proposed New Fig. 12 Company Blanket Bond Proposed Casing and CEMENT PROGRAM SIZE OF HOLE SIZE OF CASING WEIGHT PER FOOT SETTING DEPTH SACKS OF CEMENT EST. TOP 12 3/4" 8 5/8" 24# 250' 150 Circulate 7 7/8" 4 1/2" 9.5# 4600' 250 3600' Plan to drill 12 3/4" hole to 250' and run 8 5/8" 24# J-55 Casing and set with 250 sacks cement 2% CaCl; let set 12 hours. Pressure up to 800 psi, hold 15 minutes, then drill 7 7/8" hole to 4600' and log. If logs indicate formation to be productive, we will run 4 1/2" 9.5# casing to TD and set with 250 sacks cement 2% Gal 3# CaCl per sack and attempt completion.	HHHHHH	<i>HHHH</i>	HHH	HHHHH	19. Proposed Depth	19A. Formati	on	20. Rotary or C.T.
Elevations (Show whether DF, NT, etc.) 21A, Kind & Status Plug, Bond 21B, Drilling Contractor Horan Drilling Company March 23, 1966 PROPOSED CASING AND CEMENT PROGRAM SIZE OF HOLE SIZE OF CASING WEIGHT PER FOOT 12 3/4" 8 5/8" 24# 250! 150 Circulate 7 7/8" Plan to drill 12 3/4" hole to 250" and run 8 5/8" 24# J-55 Casing and set with 250 sacks cement 2% CaCl; let set 12 hours. Pressure up to 800 psi, hold 15 minutes, then drill 7 7/8" hole to 4600" and log. If logs indicate formation to be productive, we will run 4 1/2" 9.5# casing to TD and set with 250 sacks cement 2% Gel 8# CaCl per sack and attempt completion.	### 21A. Kind & Status Plug. Bend Blanket Bond Blanket Bond Blanket Bond PROPOSED CASING AND CEMENT PROGRAM SIZE OF HOLE SIZE OF CASING WEIGHT PER FOOT SETTING DEPTH SACKS OF CEMENT EST. TOP					46001	San And	res	Rotary
PROPOSED CASING AND CEMENT PROGRAM SIZE OF HOLE SIZE OF CASING WEIGHT PER FOOT SETTING DEPTH SACKS OF CEMENT EST. TOP 12 3/4" 8 5/8" 24# 250" 150 C!rculate 7 7/8" 4 1/2" 9.5# 4600" 250 3600" Plan to drill 12 3/4" hole to 250" and run 8 5/8" 24# J-55 Casing and set with 250 sacks cement 2% CaCl; let set 12 hours. Pressure up to 800 psi, hold 15 minutes, then drill 7 7/8" hole to 4600" and log. If logs indicate formation to be productive, we will run 4 1/2" 9.5# casing to TD and set with 250 sacks cement 2% Gel 8# CaCl per sack and attempt completion.	PROPOSED CASING AND CEMENT PROGRAM SIZE OF HOLE SIZE OF CASING WEIGHT PER FOOT SETTING DEPTH SACKS OF CEMENT EST. TOP 12 3/4" 8 5/8" 24# 250! 150 Circulate 7 7/8" 4 1/2" 9.5# 4600' 250 3600' Plan to drill 12 3/4" hole to 250' and run 8 5/8" 24# J-55 Casing and set with 250 sacks cement 2% CaCl; let set 12 hours. Pressure up to 800 psi, hold 15 minutes, then drill 7 7/8" hole to 4600' and log. If logs indicate formation to be productive, we will run 4 1/2" 9.5# casing to TD and set with 250 sacks cement 2% Gel 8# CaCl per sack and attempt completion.	Elevations (Show whether DI	F, RT, etc.)	21A. Kind	& Status Plug. Bond				
PROPOSED CASING AND CEMENT PROGRAM SIZE OF HOLE SIZE OF CASING WEIGHT PER FOOT SETTING DEPTH SACKS OF CEMENT EST. TOP 12 3/4" 8 5/8" 24# 250" 150 Circulate 7 7/8" Plan to drill 12 3/4" hole to 250" and run 8 5/8" 24# J-55 Casing and set with 250 sacks cement 2% CaCl; let set 12 hours. Pressure up to 800 psi, hold 15 minutes, then drill 7 7/8" hole to 4600" and log. If logs indicate formation to be productive, we will run 4 1/2" 9.5# casing to TD and set with 250 sacks cement 2% Gel 8# CaCl per sack and attempt completion.	SIZE OF HOLE SIZE OF CASING WEIGHT PER FOOT SETTING DEPTH SACKS OF CEMENT EST. TOP 12 3/4" 8 5/8" 24# 250! 150 Circulate 7 7/8" 4 1/2" 9.5# 4600! 250 3600! Plan to drill 12 3/4" hole to 250' and run 8 5/8" 24# J-55 Casing and set with 250 sacks cement 2% CaCl; let set 12 hours. Pressure up to 800 psi, hold 15 minutes, then drill 7 7/8" hole to 4600' and log. If logs indicate formation to be productive, we will run 4 1/2" 9.5# casing to TD and set with 250 sacks cement 2% Gel 8# CaCl per sack and attempt completion.	4412' GR		81 anke	t Bond	Moran Drill	ing Company	y March	23. 1966
SIZE OF HOLE SIZE OF CASING WEIGHT PER FOOT SETTING DEPTH SACKS OF CEMENT EST. TOP 12 3/4" 8 5/8" 24# 250" 150 Circulate 27 7/8" 4 1/2" 9.5# 4600" Plan to drill 12 3/4" hole to 250" and run 8 5/8" 24# J-55 Casing and set with 250 sacks cement 2% CaCl; let set 12 hours. Pressure up to 800 psi, hold 15 minutes, then drill 7 7/8" hole to 4600" and log. If logs indicate formation to be productive, we will run 4 1/2" 9.5# casing to TD and set with 250 sacks cement 2% Gel 8# CaCl per sack and attempt completion.	SIZE OF HOLE SIZE OF CASING WEIGHT PER FOOT SETTING DEPTH SACKS OF CEMENT EST. TOP 12 3/4" 8 5/8" 24# 250" 150 Circulate 7 7/8" 4 1/2" 9.5# 4600" Plan to drill 12 3/4" hole to 250" and run 8 5/8" 24# J-55 Casing and set with 250 sacks cement 2% CaCl; let set 12 hours. Pressure up to 800 psi, hold 15 minutes, then drill 7 7/8" hole to 4600" and log. If logs indicate formation to be productive, we will run 4 1/2" 9.5# casing to TD and set with 250 sacks cement 2% Gel 8# CaCl per sack and attempt completion. SEXPIRES PROPOSED PROGRAM, IF ANY. TRIDE GEOLOGIST Page March 18, 1966			Pi	POPOSED CASING AN		,	,	
Plan to drill 12 3/4" hole to 250° and run 8 5/8" 24# J-55 Casing and set with 250 sacks cement 2% CaCl; let set 12 hours. Pressure up to 800 psi, hold 15 minutes, then drill 7 7/8" hole to 4600° and log. If logs indicate formation to be productive, we will run 4 1/2" 9.5# casing to TD and set with 250 sacks cement 2% Gel 8# CaCl per sack and attempt completion. ABOVE SPACE DESCRIBE PROPOSED PROGRAM: IF PROPOSAL IS TO DEEPEN OR PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED NEW FOR COME, GIVE BLOWOUT PREVENTER PROGRAM, IF ANY. TREBY CERTIFY HONE AND PROPOSED PROGRAM: IF PROPOSAL IS TO DEEPEN OR PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED NEW FOR COME, GIVE BLOWOUT PREVENTER PROGRAM, IF ANY. TREBY CERTIFY HONE AND PROPOSED NEW FOR COME AND PROPOSED NEW FO	Plan to drill 12 3/4" hole to 250' and run 8 5/8" 24# J-55 Casing and set with 250 sacks cement 2% CaCl; let set 12 hours. Pressure up to 800 psi, hold 15 minutes, then drill 7 7/8" hole to 4600' and log. If logs indicate formation to be productive, we will run 4 1/2" 9.5# casing to TD and set with 250 sacks cement 2% Gel 8# CaCl per sack and attempt completion. NEOVE SPACE DESCRIBE PROPOSED PROGRAM: IF PROPOSAL IS TO DEEPEN OR PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED NEW PROPOSED IN THE PROPOSED PROGRAM, IF ANY. Title Geologist Date March 18, 1966								1
Plan to drill 12 3/4" hole to 250' and run 8 5/8" 24# J-55 Casing and set with 250 sacks cement 2% CaCi; let set 12 hours. Pressure up to 800 psi, hold 15 minutes, then drill 7 7/8" hole to 4600' and log. If logs indicate formation to be productive, we will run 4 1/2" 9.5# casing to TD and set with 250 sacks cement 2% Gel 8# CaCl per sack and attempt completion. ABOVE SPACE DESCRIBE PROPOSED PROGRAM: IF PROPOSAL IS TO DEEPEN OR PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED NEW FOR COVER SLOWOUT PREVENTER PROGRAM, IF ANY. TREDUCTIVE SLOWOUT PREVENTER PROGRAM: IF ANY. TREDUCTIVE STATE PROPOSED PROGRAM: IF PROPOSAL IS TO DEEPEN OR PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED NEW FOR COVER SLOWOUT PREVENTER PROGRAM, IF ANY.	Plan to drill 12 3/4" hole to 250' and run 8 5/8" 24# J-55 Casing and set with 250 sacks cement 2% CaCl; let set 12 hours. Pressure up to 800 psi, hold 15 minutes, then drill 7 7/8" hole to 4600' and log. If logs indicate formation to be productive, we will run 4 1/2" 9.5# casing to TD and set with 250 sacks cement 2% Gel 8# CaCl per sack and attempt completion. **EXPIRES** **E				WEIGHT BES ESS		DTU CACKC		
Plan to drill 12 3/4" hole to 250' and run 8 5/8" 24# J-55 Casing and set with 250 sacks cement 2% CaCl; let set 12 hours. Pressure up to 800 psi, hold 15 minutes, then drill 7 7/8" hole to 4600' and log. If logs indicate formation to be productive, we will run 4 1/2" 9.5# casing to TD and set with 250 sacks cement 2% Gel 8# CaCl per sack and attempt completion. ABOVE SPACE DESCRIBE PROPOSED PROGRAM: IF PROPOSAL IS TO DEEPEN OR PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED NEW PROPOSED REVERSED PROGRAM, IF ANY. TREDUCTIVE BLOWOUT PREVENTER PROGRAM, IF ANY. TREDUCTIVE BLOWOUT PREVENTER PROGRAM, IF ANY.	Plan to drill 12 3/4" hole to 250' and run 8 5/8" 24# J-55 Casing and set with 250 sacks cement 2% CaCl; let set 12 hours. Pressure up to 800 psi, hold 15 minutes, then drill 7 7/8" hole to 4600' and log. If logs indicate formation to be productive, we will run 4 1/2" 9.5# casing to TD and set with 250 sacks cement 2% Gel 8# CaCl per sack and attempt completion. **EXPIRES** ANDOVE SPACE DESCRIBE PROPOSED PROGRAM: IF PROPOSAL IS TO DEEPEN OR PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED NEW PROPOSED STATE PROPOSED NEW PROPOSED STATE PROPOSED NEW PROPOSED TO THE BLOWGUT PREVENTER PROGRAM, IF ANY. TENDER STATE BLOWGUT PREVENTER PROGRAM, IF ANY. THE Geologist Date March 18, 1966								†
250 sacks cement 2% CaCl; let set 12 hours. Pressure up to 800 psi, hold 15 minutes, then drill 7 7/8" hole to 4600' and log. If logs indicate formation to be productive, we will run 4 1/2" 9.5# casing to TD and set with 250 sacks cement 2% Gel 8# CaCl per sack and attempt completion. ABOVE SPACE DESCRIBE PROPOSED PROGRAM: IF PROPOSAL IS TO DEEPEN OR PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED NEW PC 20NE. GIVE BLOWOUT PREVENTER PROGRAM, IF ANY. Treby certify that the information above is true and complete to the best of my knowledge and belief.	250 sacks cement 2% CaCl; let set 12 hours. Pressure up to 800 psi, hold 15 minutes, then drill 7 7/8" hole to 4600° and log. If logs indicate formation to be productive, we will run 4 1/2" 9.5# casing to TD and set with 250 sacks cement 2% Gel 8# CaCl per sack and attempt completion. ABOVE SPACE DESCRIBE PROPOSED PROGRAM: IF PROPOSAL IS TO DEEPEN OR PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED NEW PR	12 3/4"	8 5/8	1	24#	2501	150		Circulate
ABOVE SPACE DESCRIBE PROPOSED PROGRAM: IF PROPOSAL IS TO DEEPEN OR PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED NEW PERCENT OF PROGRAM, IF ANY. Treby certify that the information above is true and complete to the best of my knowledge and belief.	ABOVE SPACE DESCRIBE PROPOSED PROGRAM: IF PROPOSAL IS TO DEEPEN OR PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED NEW PROPOSED NEW PROPOSED IN PROPOSED NEW PROP	12 3/4"	8 5/8	1	24#	2501	150		Circulate
	(This small fitte lise)	Plan to dr 250 sacks minutes, t	8 5/8: 4 1/2: rill 12 3/ cement 29 then drill ductive, v	/4" hole % CaCl; I 7 7/8"	24# 9.5# to 250' and let set 12 ho ' hole to 4600 run 4 1/2'' 9	run 8 5/8" 2 ours. Pressu of and log5# casing to	150 250 250 4# J-55 Ca re up to 8 If logs in TD and se on.	sing and 00 psi, h dicate fo t with 25	set with old 15

CONDITIONS OF APPROVAL, IF ANY: