

COUNTY	ROOSEVELT		FIELD	Chaveroo	STATE	NM
OPR	SUN OIL COMPANY				MAP	
	3 McFarland, James					
	Sec. 20, T-7-S, R-33-E				CO. ORD	
	1979' FSL, 1956' FWL of Sec.				MX 10483	
	Spd 4-23-66				CLASS	
	Cmp 5-20-66				EL	
			FORMATION	DATUM	FORMATION	DATUM
CSG & SX - TUBING						
	8 5/8"	382'	200			
	4 1/2"	4350'	225			
LOGS EL GR RA IND HC A						
			TD 4350', PBD 4335'			

IP San Andres Perfs 4159-4294' Pmpd 66 BOPD + 30 BW. Pot.
Based on 24 hr test, gravity 24.3, GOR 636.

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT.	PROP DEPTH	4500'	TYPE
DATE			

F.R. 3-24-66
PD 4500' - SA
4-25-66 Drlg. 1129'.
5-2-66 TD 4250', prep to core.
Cored 4150-4200', rec 50' dolo., w/scatt
shows.
Cored 4200-4250', rec 50' same.
5-9-66 TD 4350', PBD 4335', prep to test.
Cored 4250-4300', rec 49½' dolo & anhy.,
w/scatt good shows.
Perf @ 4159', 4162', 4176', 4181',
4184', 4195', 4199', 4222', 4229',
4234', 4237', 4241', 4249', 4254',
4263', 4269', 4272', 4276', 4280',
4286', 4290', 4294' W/1 SPI

5-16-66 TD 4350', FBD 4335', WO Pump.
Ac (4159-4294') 2000 gals.
Frac (4159-4294') 40,000 gals oil +
40,000# sd.
LOG TOPS: Anhydrite 1724', Yates 2294',
San Andres 3454', Pi Zone 4007', Slaughter
4142'.
5-23-66 TD 4350', FBD 4335', COMPLETED.