

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

HOBBS OFFICE O.C.C.

APR 14 11 27 AM '66

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-		7. Unit Agreement Name
2. Name of Operator Sun Oil Company		8. Farm or Lease Name James McFarland "A"
3. Address of Operator P. O. Box 2792, Odessa, Texas		9. Well No. 3
4. Location of Well UNIT LETTER <u>J</u> , <u>1979.5</u> FEET FROM THE <u>South</u> LINE AND <u>1955.8</u> FEET FROM THE <u>East</u> LINE, SECTION <u>20</u> TOWNSHIP <u>7 S</u> RANGE <u>33 E</u> NMPM.		10. Field and Pool, or Wildcat Undesignated
15. Elevation (Show whether DF, RT, GR, etc.) 4425' Gr.		12. County Roosevelt

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Lane Wells ran Gamma Ray densilog 100' to 4450', focused log 2200 - 4444', minifocus 2200' to 4452'. On 4-12-66 ran 140 jts. 4 1/2" OD, 9.5# casing, seated at 4450'. Cemented with 150 sacks Incor cement w/4% gel & 0.5% D-30. Fifteen Kluck centralizers 1 jt. apart 4007 to 4445'. Twenty seven Kluck scratchers 16' apart 4021' to 4436'. WOC 24 hours. Tested csg. 2000', 30 minutes, o.k. Tom Hansen ran temperature survey, top of cement 3797'.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED T. E. Mapule TITLE Area Superintendent DATE 4-12-66
APPROVED BY Joe L. [Signature] TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY: