

COUNTY	ROOSEVELT		FIELD	Chaveroo	STATE	NM
OPR	CHAMPLIN PETROLEUM COMPANY					MAP
	10 Lauck-Federal					
	Sec. 29, T-7-S, R-33-E					CO-ORD
	1980' FSL, 660' FWL of Sec.					MX 10486
	Spd 3-21-66					EL [REDACTED]
	Cmp 4-20-66					
		FORMATION		DATUM	FORMATION	DATUM
CSG & SX - TUBING						
8 5/8" 364' 250						
4 1/2" 4438' 300						
LOGS EL GR RA IND HC A						
	TD 4438', PBD 4436'					

IP San Andres Perfs 4186-4340' Pmpd 44 BOPD + 76 BW. Pot. Based on 24 hr test, gravity 24.6, GOR 1250.

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT.	PROP DEPTH	4500'	TYPE
DATE			

F.R. 3-24-66; Opr's Elev. 4442' KB
PD 4500' - SA
3-28-66 Drlg. 4033'.
4-4-66 TD 4438', PBD 4436', rec'g load.
Perf @ 4186', 4193', 4222', 4251', 4259',
4279', 4295', 4301', 4314', 4327', 4340'
W/2 SPI
Ac (4186-4340') 2500 gals.
Frac (4186-4340') 50,000 gals wtr +
40,000# sd.
4-11-66 TD 4438', PBD 4436', SD Pump Repairs.
(-950 BLW)
4-18-66 TD 4438', PBD 4436', pmpg load.
4-25-66 TD 4438', PBD 4436', WO Pot.
Pmpd 44 BO + 76 BW/24 hrs.
5-2-66 TD 4438', PBD 4436', COMPLETE.
LOG TOPS: Anhydrite 1755', Yates 2294',
Queen 2966', San Andres 3518'.