

COUNTY	ROOSEVELT	FIELD	Chaveroo	STATE	NM
OPR	CHAMPLIN PETROLEUM CO.				MAP
	11 Lauck-Federal				
	Sec. 29, T-7-S, R-33-E				CO-ORD
	1980' FSL, 1980' FWL of Sec.				MX 10487
	Spd 4-1-66		CLASS		E
	Cmp 4-23-66				
	FORMATION	DATUM	FORMATION	DATUM	
CSG & SX - TUBING					
8 5/8" 376' 250					
4 1/2" 4445' 325					
LOGS EL GR RA IND HC A					
	TD 4445'				

IP San Andres Perfs 4194-4346' Pmpd 55 BOPD + 65 BW. Pot.
Based on 24 hr test.

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT.	PROP DEPTH 4500'	TYPE
DATE		

F.R. 3-24-66
PD 4500' - SA
4-4-66 Drlg. 2897'.
4-11-66 TD 4445', WOC.
4-18-66 TD 4445', pmpg load.
Perf @ 4194', 4229', 4256', 4270', 4280',
4306', 4314', 4330', 4346' W/2 SPI
Ac (4194-4346') 2500 gals.
Frac (4194-4346') 30,000 gals wtr +
40,000# sd.
4-25-66 TD 4445', pmpg load.
Pmpd 125 BLW/24 hrs (15% oil) (-400 BLW)
5-2-66 TD 4445', COMPLETE.
(Holding for tops)
5-23-66 TD 4445', Completion Reported.
LOG TOPS: Anhydrite 1755', Yates 2309',
Queen 2987', San Andres 3547'.