

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.
New Mexico 020790

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER ☐		7. UNIT AGREEMENT NAME	
2. NAME OF OPERATOR H. L. Brown, Jr. & Clem E. George		8. FARM OR LEASE NAME Cuccia-Federal	
3. ADDRESS OF OPERATOR 704 Vaughn Building, Midland, Texas		9. WELL NO. 1	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below) At surface 990' FEL & 990' FSL of Sec. 5, T-8-S, R-37-E		10. FIELD AND POOL, OR WILDCAT Bluitt San Andres	
14. PERMIT NO.		15. ELEVATIONS (Show whether DF, RT, GR, etc.) 4046.4' GR	
		12. COUNTY OR PARISH Roosevelt	
		13. STATE N. M.	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐	WATER SHUT-OFF ☒	REPAIRING WELL ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETE ☐	FRACTURE TREATMENT ☒	ALTERING CASING ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☐	SHOOTING OR ACIDIZING ☒	ABANDONMENT* ☐
REPAIR WELL ☐	CHANGE PLANS ☐	(Other) ☐	

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

4/4/66 - Reached total depth of 4470' at 8:30 A.M. Ran 4460.5' of 4-1/2", 10.5 lb., J-55, 8 rd. thrd. seamless, short thread & coupling, used casing at 4470' and cemented with 250 sacks of 50-50 Posmix "S", 2% Jel, and 8 lb. salt per sack. Plug down at 10 A.M., April 5, 1966. W. O. C. 24 hours.

4/6/66 - Drilled out at 10 A.M. to 4469'.

4/11/66- Tested casing at 4000 lb. for 30 minutes. Test O. K. Perforated: 4462-4446 1/2'; 4431 1/2'-4403'; 4388-4379 1/2'; 4368 1/2'-4344 1/2'; 4327 1/2'-4313 1/2'. Acidized with 2,000 gallons of breakdown acid. Sandfrac with 30,000 gallons jelled brine water and 30,000 lb. of 20-40 sand.

4/12/66- Swabbing and cleaning.

18. I hereby certify that the foregoing is true and correct

SIGNED *J. L. Gordon* TITLE Agent DATE April 12, 1966
(This space for Federal or State office use)

APPROVED BY _____ TITLE _____
CONDITIONS OF APPROVAL, IF ANY:

APPROVED

APR 12 1966

*See Instructions on Reverse Side

J. L. GORDON
ACTING DISTRICT ENGINEER

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.