(May 1963)	UN TED STATES	SUBMIT IN TRIP! ATE	Form apple Budget Budge	reau No. 42-R1424.
DEF	PARTME TO OF THE INTE		5. LEASE DESIGNATI	0 AND SERIAL NO.
	GEOLOGICAL SURVEY		_	THE OR TRIBE NAME
SUNDRY (Do not use this form fo Use "A	NOTICES AND REPORT or proposals to drill or to deepen por APPLICATION FOR PERMIT— TERMS	de back to be difficultificervoir.		
1. OIL GE GAS			7. UNIT AGREEMENT	NAME
	THER TO THE PARTY OF THE PARTY	· ·	8. FARM OR LEASE	NAME
2. NAME OF OPERATOR ROTT-OPERATOR: Champlin Petroleum Company Warren American Oil Company		Lack-Poderal		
3. ADDRESS OF OPERATOR			9. WELL NO.	
P. O. Box 1797, M	idiand, Texas ocation clearly and in accordance with	any State requirements	10. FIELD AND POOI	OR WILDCAT
See also space 17 helow )	& 1980' FML, Section 2		11. SEC., T., E., M., SURVEY OR A	OR BLK. AND REA
			12. COUNTY OR PAR	7-8, R-33-4
14. PERMIT NO.	15. BLEVATIONS (Show wheth	er DF, RT, GR, etc.)	Rodanvelt	New Mexico
16. Ch	eck Appropriate Box To Indica	te Nature of Notice, Report, or	Other Data	
NOTICE	OF INTENTION TO:	SUBSE	QUENT REPORT OF:	<del></del> -
TEST WATER SHUT-OFF	PULL OR ALTER CASING	WATER SHUT-OFF	9	NG WELL
FRACTURE TREAT	MULTIPLE COMPLETE	FRACTURE TREATMENT SHOOTING OR ACIDIZING	ALTERIN	G CASING
SHOOT OR ACIDIZE REPAIR WELL	ABANDON* CHANGE PLANS	(Other) Specialing		X
(Other)		(Norg: Report resul	its of multiple completingletion Report and Log	lon on Well g form.)
sitton & Morton	Drilling Co. spudded	38:00 P.M. 4-13-66. B vice Cucing At 370'.	es, including estimated ical depths for all mar rilled 12-1/4 Comented with	date of starting any kers and zones perti
Sitton & Morton to 373'. Set 3 of regular plus Plus down at 7:	Drilling Co. spushed	38:00 P.M. 4-13-66. Divice Cacing At 370'. od 1/4# Flownesh per sed casing & blow-out p	es, including estimated ical depths for all mar rilled 12-1/4 Comented with	iple 250 eachs ed cement.
sitton & Morton to 373'. Set 8 of regular plus Plus down at 7: water for 30 mi	Drilling Co. spended : -5/8", 20f Limited Ser -25 Calcium Chloride & -5/8. A. 4-14-66. Test	Bioc P.M. 4-13-66. Divice Cacing At 370'. and 1/4# Planeeal per and casing & blow-out parts.	es, including estimated cical depths for all mar rilled 12-1/4 Comented with circular	iple 250 sachs ed cument.
sitton & Morton to 373'. Set 8 of regular plus Plus down at 7: water for 30 mi	Drilling Co. specified of 15/8", 20f Limited Ser 25 Calcium Chloride & 45 A.M. 4-14-66. Test nutes 312 Ridnight 4-1	Bioc P.M. 4-13-66. Divice Cacing At 370'. and 1/4# Planeeal per and casing & blow-out parts.	es, including estimated cical depths for all mar rilled 12-1/4 Comented with circular	iple 250 eachs ed cement.
sitton & Morton to 373'. Set 8 of regular plus Plus down at 7: water for 30 mi	Drilling Co. specified of 15/8", 20f Limited Ser 25 Calcium Chloride & 45 A.M. 4-14-66. Test nutes 312 Ridnight 4-1	Bioc P.M. 4-13-66. Divice Cacing At 370'. and 1/4# Planeeal per and casing & blow-out parts.	es, including estimated cical depths for all mar rilled 12-1/4 Comented with circular	inle 250 canho ed coment.
sitton & Morton to 373'. Set 8 of regular plus Plus down at 7: water for 30 mi	Drilling Co. specified of 15/8", 20f Limited Ser 25 Calcium Chloride & 45 A.M. 4-14-66. Test nutes 312 Ridnight 4-1	Bioc P.M. 4-13-66. Divice Cacing At 370'. and 1/4# Planeeal per and casing & blow-out parts.	es, including estimated cical depths for all mar rilled 12-1/4 Comented with circular	inle 250 canho ed coment.
sitton & Morton to 373'. Set 8 of regular plus Plus down at 7: water for 30 mi	Drilling Co. specified of 15/8", 20f Limited Ser 25 Calcium Chloride & 45 A.M. 4-14-66. Test nutes 312 Ridnight 4-1	Bioc P.M. 4-13-66. Divice Cacing At 370'. and 1/4# Planeeal per and casing & blow-out parts.	es, including estimated cical depths for all mar rilled 12-1/4 Comented with circular	inle 250 canho ed coment.
sitton & Morton to 373'. Set 8 of regular plus Plus down at 7: water for 30 mi	Drilling Co. specified of 15/8", 20f Limited Ser 25 Calcium Chloride & 45 A.M. 4-14-66. Test nutes 312 Ridnight 4-1	Bioc P.M. 4-13-66. Divice Cacing At 370'. and 1/4# Planeeal per and casing & blow-out parts.	es, including estimated cical depths for all mar rilled 12-1/4 Comented with circular	iple 250 eachs ed cement.
sitton & Morton to 373'. Set 8 of regular plus Plus down at 7: water for 30 mi	Drilling Co. specified of 15/8", 20f Limited Ser 25 Calcium Chloride & 45 A.M. 4-14-66. Test nutes 312 Ridnight 4-1	Bioc P.M. 4-13-66. Divice Cacing At 370'. and 1/4# Planeeal per and casing & blow-out parts.	es, including estimated cical depths for all mar rilled 12-1/4 Comented with circular	iple 250 eachs ed cement.
sitton & Morton to 373'. Set 8 of regular plus Plus down at 7: water for 30 mi	Drilling Co. specified of 15/8", 20f Limited Ser 25 Calcium Chloride & 45 A.M. 4-14-66. Test nutes 312 Ridnight 4-1	Bioc P.M. 4-13-66. Divice Cacing At 370'. and 1/4# Planeeal per and casing & blow-out parts.	es, including estimated cical depths for all mar rilled 12-1/4 Comented with circular	inle 250 canho ed coment.
sitton & Morton to 373'. Set 8 of regular plus Plus down at 7: water for 30 mi	Drilling Co. spudded  -5/8", 20f Limited Ser  25 Calcium Chloride &  45 A.M. 4-14-66. Test  Rutes 312 Ridnight 4-1  bole below surface an	Bioc P.M. 4-13-66. Divice Cacing At 370'. and 1/4# Planeeal per and casing & blow-out parts.	es, including estimated cical depths for all mar rilled 12-1/4 Comented with circular	iple 250 eachs ed cement.
sitton & Horton to 373'. Set 8 of regular plus Plus down at 7: water for 30 mi	Drilling Co. spudded  -5/8", 20f Limited Ser  25 Calcium Chloride &  45 A.M. 4-14-66. Test  Rutes 312 Midnight 4-1  bole below surface an	Bioc P.M. 4-13-66. Divice Cacing At 370'. and 1/4# Planeeal per and casing & blow-out parts.	es, including estimated ical depths for all mar rilled 12-1/4 Commented with all. Circulal revenues to 6	iple 250 sachs ed cument.
sitton & Borton to 373'. Set 8 of regular plus Plus down at 7: water for 30 mi	a Drilling Co. specified in 5/8", 20% Limited Ser 2% Calcium Chloride & 45 A.M. 4-14-66. Test Inutes 312 Midnight 4-1 hole below surface 24 regoing is true and correct TITLE.	Bicc P.M. 4-13-66. Bivice Cacing At 370'.  14 1/4 Flowers per a  ed casing & blow-out p  4-66. Test okey.	es, including estimated ical depths for all mar rilled 12-1/4 Commented with all. Circulal revenues to 6	iple 250 sachs ed cument.
Bitton & Horton to 373'. Set 8 of regular plus Plus down at 7: water for 30 mi Drilling 7-1/8"	regoing is true and correct  H. H. Brown  TITLE  State office use)	Biox P.M. 4-13-66. B. vice Cacing At 370'. and 1/4# Flowscal per a ed casing & blow-out p 4-66. Test okay.	es, including estimated ical depths for all mar rilled 12-1/4 Commented with all. Circulal revenues to 6	tole 250 eachs ed cement. 100# with

\*See Instructions on Reverse Side

APR 19 1966

## Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State of Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE, 1963 -- C-685229

867-851

99. 1

ijį

. 6. **c.**