

DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" of such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR
KERN COUNTY LAND COMPANY

3. ADDRESS OF OPERATOR
413 FIRST STATE BANK BLDG. MIDLAND, TEXAS

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface
1920' FNL & 660' FEL Sec 27 (Unit H, SE 1/4, NE 1/4)

5. LEASE DESIGNATION AND SERIAL NO.
NM 0127782

6. IF INDIAN, ALLOTTEE OR TRIBE NAME
—

7. UNIT AGREEMENT NAME
—

8. FIRM OR LEASE NAME
FEDERAL 27

9. WELL NO.
1

10. FIELD AND POOL, OR WILDCAT
CHAVEZCO-SAN ANDRES

11. SEC., T., R., M., OR BLM. AND SURVEY OR AREA
Sec 27, T7S, R53E N44M

12. COUNTY OR PARISH
ROOSEVELT

13. STATE
N.M.

14. PERMIT NO.

15. ELEVATIONS (Show whether SP, RT, OR, etc.)
To be furnished later.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐	WATER SHUT-OFF ☐	REPAIRING WELL ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETE ☐	FRACTURE TREATMENT ☐	ALTERING CASING ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☐	SHOOTING OR ACIDIZING ☐	ABANDONMENT* ☐
REPAIR WELL ☐	CHANGE PLANS ☒	(Other) ☐	
(Other) ☐		(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)	

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. Drill 8³/₄" hole to 1850' ±. Cement 7" casing to surface w/ 350 sx Incor cement plus 8% gel. Tail in w/ 100 sx Incor treated w/ 2% CaCl₂. Test casing to 1000 psi for 30 mins.
2. Drill 6¹/₄" hole to 4400' ± T.D. Run logs. Cement 4¹/₂" casing at 4400' w/ 230 sx Incor plus 8% gel saturated salt cement. Tail in w/ 100 sx Incor saturated salt cement.
3. Perforate & stimulate for commercial production.

18. I hereby certify that the foregoing is true and correct

SIGNED C. J. Carter TITLE DISTRICT ENGINEER DATE 6-15-66

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

