

DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY - D. C. C.

STANDARD NOTICES AND REPORTS

(Do not use this form for proposals to drill or to develop oil or gas to a different reservoir.
Use "APPLICATION FOR PERMIT TO DRILL" for such proposals.)

5. LEASE DESIGNATION

NM 0127112

6. IF INDIAN, ALLOTTEE OR TRUST NAME

7. UNIT AGREEMENT NAME

8. NAME OF LEASEE NAME

FEDERAL 27

9. WELL NO.

3

10. FIELD AND FOOT OR WILDCAT

CONFESSION - SAN ANTONIO

11. ELEC. T. M. OR SURV. AND SURVEY OR AREA

SEC 27, T12, R10E, N14E

12. COUNTY OR PARISH 13. STATE

ROBERTSON N.M.

1. TYPE OF OPERATION
OIL ☒ GAS ☐ OTHER ☐

2. NAME OF OPERATOR
MEXICO CITY LAND COMPANY

3. ADDRESS OF OPERATOR

445 FIFTH STREET BANK BLDG. HOUSTON, TEXAS

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
at surface

500' FNL & FEL SEC. 27 (Unit A 12/10, 12/10)

14. PERMIT NO.

15. ELEVATIONS (Show whether DT, ST, OR, etc.)

To be furnished later.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐
☐
☐
☐
☐

PULL OR ALTER CASING

☐
☐
☐
☐
☐

MULTIPLE COMPLETION

ABANDON*

CHANGE PLANS

WATER SHUT-OFF

☐
☐
☐

FRACURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

(Note: Report results of multiple completion or Well Completion or Recompletion Report and Test Report)

REPAIRING WELL

☐
☐
☐
☐
☐

ADJUSTING CASING

ABANDONMENT*

17. INDICATE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. Drill 8 3/4" hole to 1050'. Cement 7" casing to surface w/ 250 sx Incon cement plus 8% gel. Tail in w/ 100 sx Incon treated w/ 2% Cacl₂. Test casing to 1000 psi for 30 mins.
2. Drill 6 1/2" hole to 4400' T.D. Run logs. Cement 4 1/2" casing at 4400' w/ 230 sx Incon plus 8% gel saturated salt cement. Tail in w/ 100 sx Incon saturated salt cement.
3. Perforate & stimulate for commercial production.

18. I hereby certify that the foregoing is true and correct

SIGNED C. E. Carter

TITLE DISTRICT ENGINEER

DATE 6-13-66

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

APPROVED

JUN 16 1966

A. R. BROWN
DISTRICT ENGINEER