

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE\*  
(Other instructions on reverse side)

Form approved.  
Budget Bureau No. 42-R1424.

~~SUNDAY NOTICES AND~~ REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR KERN COUNTY LAND CO.	8. FARM OR LEASE NAME FEDERAL 23
3. ADDRESS OF OPERATOR 418 FIRST STATE BANK BLDG. MIDLAND,	9. WELL NO. 8
4. LOCATION OF WELL (See also space 17) At surface	10. FIELD AND POOL, OR WILDCAT CHAVEZ SAN ANDRES
14. PERMIT NO. 660 FCL 5 1980 FSL SEC 23 UNIT I NE 1/4 SE 1/4	11. SEC. T. B. M. OR BLK. AND SURVEY OR AREA 23 T75 R33E N4PM
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 4336.5 GR	12. COUNTY OR PARISH ROOSEVELT
	13. STATE NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF <input type="checkbox"/>	PULL OR ALTER CASING <input type="checkbox"/>
FRACTURE TREAT <input type="checkbox"/>	MULTIPLE COMPLETE <input type="checkbox"/>
SHOOT OR ACIDIZE <input type="checkbox"/>	ABANDON* <input type="checkbox"/>
REPAIR WELL <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
(Other) <input type="checkbox"/>	

SUBSEQUENT REPORT OF:

WATER SHUT-OFF <input checked="" type="checkbox"/>	REPAIRING WELL <input type="checkbox"/>
FRACTURE TREATMENT <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
SHOOTING OR ACIDIZING <input type="checkbox"/>	ABANDONMENT* <input type="checkbox"/>
(Other) <input type="checkbox"/>	

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

REACHED T.D. 4450' ON 7-17-66. LOGGED WELL.  
RAN 4 1/2" 9.5# J-55 CASING AND CEMENTED AT  
4450' WITH 250 SX INCOR SALT SATURATED  
CEMENT + 8% GEL AND 100 SX INCOR NEAT  
SALT SATURATED CEMENT. PLUG DOWN 6:15 PM,  
7-17-66. TESTED CASING TO 2000 PSI FOR 30  
MINUTES ON 7-17-66. - HELD OKAY.

18. I hereby certify that the foregoing is true and correct

SIGNED Gayle S. Sarsy TITLE PROD. SECRETARY DATE 8-18-66

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side

APPROVED

AUG 22 1966

J. L. GORDON  
ACTING DISTRICT ENGINEER



