

July 1966)

DEPARTMENT OF THE INTERIOR

GEOLOGICAL SURVEY

SUBMIT IN DUPLICATE
(Other instructions on
verse s.de)

BUDGET APPROVAL
Budget Bureau No. 45-41-21

5. LEASE DESIGNATION AND ACREAGE NO.

NM 0107997-8

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. ☐ OIL WELL ☒ GAS WELL ☐ OTHER

2. NAME OF OPERATOR

KERN COUNTY LAND CO.

3. ADDRESS OF OPERATOR

413 FIRST STATE BANK MIDLAND TEXAS

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

FEDERAL 23

9. WELL NO.

13

10. FIELD AND POOL OF WELL

CHIVEROO SAN ANGELES

11. SEC. T. R. S. OF LAND AND
SURVEY OR AREA

650' FNL : 1980' FNL SEC 23 UNIT 13 NW 1/4 NE 1/4 23 T7S R33E N19W

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, CR, etc.)

TO BE FURNISHED LATER

12. COUNTY OR PARISH, 13. STATE

PROSELYT N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐

PULL OR ALTER CASING

☐

FRACTURE TREAT

☐

MULTIPLE COMPLETE

☐

SHOOT OR ACIDIZE

☐

ABANDON*

☐

REPAIR WELL

☐

CHANGE PLANS

☐

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

☒

REPAIRING WELL

☐

FRACTURE TREATMENT

☐

ALTERING CASING

☐

SHOOTING OR ACIDIZING

☐

ABANDONING

☐

(Other)

(Note: Report results of multiple completion or well
Completion or Recompletion Report and Log Form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting and proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and labels pertinent to this work.)

SPUD 8:45 PM, 8-20-66

CEMENTED 7" 20" CASING AT 1825' WITH
350 SX INROR CEMENT, PLUG DOWN 1:30 AM,
8-21-66. CEMENT DID NOT CIRCULATE.

TOPPED WITH 30 SX CEMENT. WOC 15 HRS.

TESTED CASING TO 1000 PSI FOR 30 MINUTES

HOLD OKAY.

18. I hereby certify that the foregoing is true and correct

SIGNED

Ray L. Dancy

TITLE

PROD. SECRETARY

DATE

8-24-66

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

APPROVED

AUG 25 1966

J. L. GORDON
ACTING DISTRICT ENGINEER