Form 9-331					TORON	
(May 1963)	UNI	TED STATES.	SUBMPF IN TR		Form approved Budget Bureau	No. 42-R1.22
	DEPARTMEN GEOL	OGICAL SURVEY	verse side)		NM NINGG	nd serial no.
SI	UNDRY NOTICES	AND REPORTS	ON WELLS		6. IF INDIAN, ALLOTTEE	OR TRIBE NAME
(Do not use	this form for proposals to Use "APPLICATION	drill or to deepen or plug FOR PERMIT—" for such	back to a different reser	voir#		
OIL GAS		,	William .		7. UNIT AGREEMENT NAM	E
WELL X WE		_			8. FARM OR LEASE NAME	·
KERN (	ounty Land	160.	£.		FEDERAL 23	)
418 FIRS	T STATE BA	oux Bldg 1	AIDIAND TA	CAS	9. WELL NO.	
LOCATION OF WELL See also space 17 At surface	L (Report location clearly below.)	and in accordance with an	y State requirements.*		10. FIELD AND POOL, OR	WILDCAT
_, ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,				Š	11. SEC., T., E., M., OR BLI SURVEY OR AREA	E, AND
LO ENI È	1980' FEL S	60 23 Unit	R NW/A NE	A .	an - 1 Dan	: 4 Ninada
PERMIT NO.	15.	ELEVATIONS (Show whether )	DF, RT, GR, etc.)	4		S NWPA
	T	o BG FIRNISH	ed later	<u> </u>	Kossevelt	N.M.
<b>).</b>		riate Box To Indicate	Nature of Notice, Re	• •	and the second second second	V.
miliam was milia haya	NOTICE OF INTENTION T				INT REPORT OF:	
TEST WATER SHU		R ALTER CASING	WATER SHUT-OFF FRACTURE TREAT		REPAIRING WE	·
SHOOT OR ACIDIZ			SHOOTING OR ACT	IDIZING	ABANDONMENT	•
REPAIR WELL (Other)	CHANGE	L PLANS	(Other) (Note: Rep	port results o	of multiple completion on tion Report and Log form.	Well
DESCRIBE PROPOSE proposed work, nent to this wor	D OR COMPLETED OPERATION If well is directionally o	s (Clearly state all pertine irilled, give subsurface loc				
Du 83/4"	HOLE TO 18	Bso't. Cem	ENT TO SUG	ZFACE	เม/ลถกระ	
SCAR CE						
	ment + 8%	o GEL. TAIL	IN W/1005			
HH 2%	MENT + 896 CACIZ. TES	o GGL. TAIL OT CASING T	IN W/1005	x N6/	AT TREATED	· ;
1+H 2%	MENT + 896 CACIZ. TES HOLE TO 440	o GGL. TAIL OT CASING T O'! TD. RU	o 1000 psi N Logs. Cen	nent	TREATED	· ;
1+4 2%	MENT + 896 CACIZ. TES	o GGL. TAIL OT CASING T O'! TD. RU	o 1000 psi N Logs. Cen	nent	TREATED	· ;
144 2% 14400't	ment + 896 Caclz. Tes Hole to 440 w/180 sx I	o GGL. TAIL OT CASING T OO'! TD. RU Incor Pous	IN W/1005 TO 1000 PSI N Logs. Cen 8% GEL SA	NET TURATE	TREATED 4½ CASING ED SAGT	· ;
144 2% 14400't 1 14400't 1	MENT + 89% CACIZ. TES HOLE TO 440 W/180 SX I	o GGL. TAIL OT CASING T OO'! TD. RU INCOR PLUS ISX INCOR	IN W/1005 TO 1000 PSI N LOGS. CEN 8% GSL SA SATURATED	NEWT TURATE CEME	TREATED 4½ CASING ED SART NT:	· ;
1+14 2% 16 6/4" 1 14400't 1060+. TA	ment + 896 Caclz. Tes Hole to 440 w/180 sx I	o GGL. TAIL OT CASING T OO'! TD. RU INCOR PLUS ISX INCOR	IN W/1005 TO 1000 PSI N LOGS. CEN 8% GSL SA SATURATED	NEWT TURATE CEME	TREATED 4½ CASING ED SART NT:	· ;
144 2% 144 14400't 1 nent. TA	MENT + 89% CACIZ. TES HOLE TO 440 W/180 SX I	o GGL. TAIL OT CASING T OO'! TD. RU INCOR PLUS ISX INCOR	IN W/1005 TO 1000 PSI N LOGS. CEN 8% GSL SA SATURATED	NEWT TURATE CEME	TREATED 4½ CASING ED SART NT:	·
144 2% 14400't 1 14400't 1	MENT + 89% CACIZ. TES HOLE TO 440 W/180 SX I	o GGL. TAIL OT CASING T OO'! TD. RU INCOR PLUS ISX INCOR	IN W/1005 TO 1000 PSI N LOGS. CEN 8% GSL SA SATURATED	NEWT TURATE CEME	TREATED 4½ CASING ED SART NT:	· ;
144 2% LL 6/4" 1 4400't nent. Ta	MENT + 89% CACIZ. TES HOLE TO 440 W/180 SX I	o GGL. TAIL OT CASING T OO'! TD. RU INCOR PLUS ISX INCOR	IN W/1005 TO 1000 PSI N LOGS. CEN 8% GSL SA SATURATED	NEWT TURATE CEME	TREATED 4½ CASING ED SART NT:	· ;
1+4 2% LL 6/4" 1 4400't nent. TA	MENT + 89% CACIZ. TES HOLE TO 440 W/180 SX I	o GGL. TAIL OT CASING T OO'! TD. RU INCOR PLUS ISX INCOR	IN W/1005 TO 1000 PSI N LOGS. CEN 8% GSL SA SATURATED	NEWT TURATE CEME	TREATED 4½ CASING ED SART NT:	· ;
1+14 2% LL 6/4" 1 LH400'± NEW+. TA	MENT + 896 CACIZ. TES HOLE TO 440 W/180 SX I	o GGL. TAIL OT CASING T OO'! TD. RU INCOR PLUS ISX INCOR	IN W/1005 TO 1000 PSI N LOGS. CEN 8% GSL SA SATURATED	NEWT TURATE CEME	TREATED 4½ CASING ED SART NT:	· ;
144 2% ILL 614" ILL 6	MENT + 89% CACIZ. TES HOLE TO 440 W/180 SX I ML IN W/100 AND STIMU	T CASING TO CASING TO CASING TO RUS PLUS POR CE	IN W/1005 TO 1000 PSI N LOGS. CEN 8% GSL SA SATURATED	NEWT TURATE CEME	TREATED 4½ CASING ED SART NT:	· ;
1+4 2% 14 6 1/4" 1 14400't 10 FORATS.	MENT + 896 CACIZ. TES HOLE TO 440 W/180 SX I	T CASING TO COST TO COR PLUS SX FACOR LATE FOR CE	IN W/1005 TO 1000 PSI N LOGS. CEN 8% GSL SA SATURATED OMMERCIAL T	nent Turace Ceme Droduc	TREATED  41/2 CASING  ED SART  HIEW.	
HH 2%  LL 6/4"  HHOO'T  NENT. TA  LACRATE  Thereby corres to  SIGNOON WA	MENT + 89% CACIZ. TES HOLE TO 440 W/180 SX I ALL IN W/100 AND STIMU	T CASING TO COST TO COR PLUS SX FACOR LATE FOR CE	IN W/1005 TO 1000 PSI N LOGS. CEN 8% GSL SA SATURATED	nent Turace Ceme Droduc	TREATED  41/2 CASING  ED SART  HIEW.	
This space for F	MENT + 89%  CACIZ. TES  HOLE TO 440  W/180 SX I  MIL IN W/100  AND STIMU  hat the foregoing is true s  MAK KAMA  ederal or State office use)	T CASING TO COST TO COR PLUS SX FACOR LATE FOR CE	IN W/1005 TO 1000 PSI N LOGS. CEN 8% GSL SA SATURATED OMMERCIAL T	nent Turace Ceme Droduc	TREATED  41/2 CASING  ED SART  HIEW.	
This space for F	MENT + 89% CACIZ. TES HOLE TO 440 W/180 SX I NIL IN W/100 AND STIMU hat the foregoing is true s	T CASING TO CASING TO COR PLUS  SX FILOR LATE POR CE	IN W/1005 TO 1000 PSI N LOGS. CEN 8% GSL SA SATURATED OMMERCIAL T	nent Turace Ceme Droduc	TREATED  41/2 CASING  ED SART  HIEW.	
Thereby certay to signed with the space for F	MENT + 89%  CACIZ. TES  HOLE TO 440  W/180 SX I  MIL IN W/100  AND STIMU  hat the foregoing is true s  MAK KAMA  ederal or State office use)	TITLE	IN W/1005 TO 1000 PSI N LOGS. CEN 8% GSL SA SATURATED OMMERCIAL TO	nent Turace Ceme Droduc	TREATED  41/2 CASING  ED SART  HIEW.	
I hereby certay to signed with a pare for F	MENT + 89%  CACIZ. TES  HOLE TO 440  W/180 SX I  MIL IN W/100  AND STIMU  hat the foregoing is true s  MAK KAMA  ederal or State office use)	TITLE	IN W/1005 TO 1000 PSI N LOGS. CEN 8% GSL SA SATURATED OMMERCIAL T	nent Turace Ceme Droduc	TREATED  41/2 CASING  ED SART  HIEW.	