

OCT 11 11 5 AM '66

Form 9-331
(May 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE-
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐		7. UNIT AGREEMENT NAME	
2. NAME OF OPERATOR KERN COUNTY LAND CO.		8. FARM OR LEASE NAME FEDERAL 22	
3. ADDRESS OF OPERATOR MIDLAND TEXAS, WILFORD STATE BANK		9. WELL NO. 3	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface		10. FIELD AND POOL, OR WILDCAT CHANDLER-SEANADRES	
14. PERMIT NO. 660 FWL; 660' FSL SEC. 22 UNIT M SW/4 SW/4		11. SEC., T., R., M., OR BLM. AND SURVEY OR AREA 22-75-336 NM PM	
15. ELEVATIONS (Show whether DF, RT, CR, etc.) TO BE FURNISHED LATER		12. COUNTY OR PARISH ROOSEVELT	
		13. STATE N.M.	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETE ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☐
REPAIR WELL ☐	CHANGE PLANS ☒
(Other) ☐	

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐	REPAIRING WELL ☐
FRACTURE TREATMENT ☐	ALTERING CASING ☐
SHOOTING OR ACIDIZING ☐	ABANDONMENT* ☐
(Other) ☐	

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

DRILL 8 3/4" HOLE TO 1850'±. CEMENT CASING TO SURFACE W/ 300 SK INCOR CEMENT + 8% GEL. TAIL IN W/100 SK NEAT + 2% CACL2. TEST CASING TO 1000 PSI.

DRILL 6 1/2" HOLE TO 4400'± TD. RUN LOGS. CEMENT 4 1/2" CASING AT 4400'± W/180 SK SALT SATURATED + 8% GEL AND 100 SK INCOR NEAT + 10% SALT. PERFORATE & STIMULATE FOR COMMERCIAL PRODUCTION.

18. I hereby certify that the foregoing is true and correct

SIGNED Gay L. Hays TITLE PROD. SECRETARY DATE 10-6-66

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____

DATE _____

APPROVED

*See Instructions on Reverse

007-7 1966
A. F. BROWN
DISTRICT ENGINEER