

Form 4-331
(May 1963)

OCT 11 1966
U.S. DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 044701-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

FEDERAL 22

9. WELL NO.

10. FIELD AND POOL, OR WILDCAT

CHADWOOD-SAN ANGELES

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

22-75-336-NMNM

12. COUNTY OR PARISH 13. STATE

TO BE FURNISHED LATER ROOSEVELT N.M.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT" for such proposals.)

1.

OIL WELL ☒ GAS WELL ☐ OTHER

2. NAME OF OPERATOR

KERN COUNTY LAND CO.

3. ADDRESS OF OPERATOR

418 FIRST STATE BANK, MIDLAND, TEXAS

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)
At surface

1980' FUEL; 1980' FSL, SEC 22 UNIT K, NE 1/4 SW 1/4

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

TO BE FURNISHED LATER ROOSEVELT N.M.

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

SUBSEQUENT REPORT OF:

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

DRILL 8 3/4" HOLE TO 1850'±. CEMENT CASING TO SURFACE W/300 SK INCOR CEMENT + 8% GCL. TAIL IN W/100 SK NEAT + 2% GCL. TEST CASING TO 1000 PSI.

DRILL 6 1/4" HOLE TO 4400'±TD. RUN LOGS. CEMENT 4 1/2" CASING AT 4400'± W/180 SK SALT SATURATED + 8% GCL AND 100 SK INCOR NEAT + 10% SALT. PERFORATE & STIMULATE FOR COMMERCIAL PRODUCTION.

18. I hereby certify that the foregoing is true and correct

SIGNED

J. L. Massey

TITLE

PRODUCTION SECRETARY

DATE

10-6-66

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

APPROVED
OCT 7 1966
A. H. BROWN
DISTRICT ENGINEER