

(Form 10-53)
(May 1953)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT REVERSE SIDE
(Other instructions on reverse side)
HOBBS

Form 10-53
Revised March 22, 1961
5. LEASE DESIGNATION AND ZONE NO.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT" for such proposals.)

SEP 27 10 17 AM '66

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR HARRIS COUNTY LAND CO.	8. NAME OF LEASE NAME FLORES 22
3. ADDRESS OF OPERATOR 1112 FIRST ST. STATE BARRACADE, MOBILE, ALA.	9. WELL NO. 5
1. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface	10. FIELD AND POOL, OR VICINITY COLUMBIA - FLORES
14. PERMIT NO. 660' FUEL & 1980' FSL SEC. 22 UNIT 1 NW/4 SW/4	11. SEC., T., R., M., OR BLM. AND SURVEY OR ALIAS 22-78-22-10-22
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 4403' KB	12. COUNTY OR PARISH ALABAMA

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETION

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONING WELL

(NOTE: Report results of multiple completion or Well Completion or Recompletion Report and Log Form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting and proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

DRILL 3 3/4" HOLE TO 1050' ±. CEMENT CASING TO SURFACE.
W/ 300 SX INCOB CEMENT PLUS 8% GEL. TAIL IN W/100 SX
INCOB HEAT TREATED W/2% PAC 2. TEST CASING TO
1000 psi.

DRILL 6 1/4" HOLE TO 4400' ± TD. RUN LOGS. CEMENT 4 1/2"
CASING AT 4400' ± W/ 100 SX INCOB + 8% GEL SALT SOLUTION
CEMENT. TAIL IN W/100 SX INCOB 10% SALT CEMENT.

SEPARATE AND STIMULATE FOR COMMERCIAL PRODUCTION

18. I hereby certify that the foregoing is true and correct

SIGNED

Ray E. Mearns

TITLE

Production Secretary

DATE

9-21-66

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side

