

COUNTY	ROOSEVELT FIELD Wildcat			STATE NM
OPR	ANTWEIL, MORRIS R.			MAP
	1 Capitan			CO-ORD
	Sec. 8, T-7-S, R-34-E			MX 10548
	1980' FSL, 660' FWL of Sec.			
	Spd 4-11-66			
	Cmp 9-28-66			
CSG & SX - TUBING	FORMATION	DATUM	FORMATION	DATUM
8 5/8" 403' 300				
4 1/2" 4289' 325				
LOGS EL GR RA IND HC A	TD 4290'			
PLUGGED & ABANDONED				

Distribution limited and publication prohibited by subscribers' agreement.
 Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. PROP DEPTH 4500' TYPE
 DATE

F.R. 4-14-66
 PD 4500' - SA
 4-18-66 Drlg. 3920' anhy & dolo.
 4-25-66 TD 4290', PBD 4248', prep Acid.
 Cored 4140-4215', rec 75' being:
 53' dolo; 22' anhy.
 Cored 4215-90', rec 75' dolo & lm.,
 w/scatt shows oil & wtr.
 Perf @ 4030½', 4052', 4077', 4132½',
 4142', 4149½', 4155', 4162', 4172' W/2 SPI
 5-2-66 TD 4290', PBD 4248', swbg load.
 Acid (4030½-4172') 1500 gals.
 Swbd dry, w/sli show oil.
 Frac (4030½-4172') 30,000 gals oil +
 30,000# sd.
 Swbd 273 BLO/24 hrs

ROOSEVELT Wildcat NM
ANTWEIL, MORRIS L., #1 Captain

Sec. 8-7S-34E
Page #2

5-9-66 TD 4290', PBD 4248', TO Pump.
Swbd & Flwd 24 ELO/4½ hrs.
5-16-66 TD 4290', PBD 4248', SI BHP.
Pmpd 13 BF/10½ hrs (70% wtr, 30% load)
5-23-66 TD 4290', PBD 4248', tstg.
Pmpd 10 ELO/25 hrs.
5-31-66 TD 4290', PBD 4248', SI.
Pmpd 34 ELO/24 hrs.
6-6-66 TD 4290', PBD 4248', TO Pump.
Pmpd 6.68 BO + 3.34 BW/24 hrs.
6-16-66 TD 4290', PBD 4248', Testing.
Pmpd & Flwd 1 ELO + 1 BW/24 hrs. (4030½-4172')
6-20-66 TD 4290', PBD 4248', SI.
6-27-66 TD 4290', PBD 4248', SI.
7-5-66 TD 4290', PBD 4248', tstg.

Set Pkr @ 4117'
Acid (4132½-72') 5000 gals + 8 Tons CO₂
Swbd & Flwd 144 ELO/9 hrs & swbd dry
Perf @ 4122', 4124', 4126', 4129', 4132',
4139', 4141', 4145', 4146', 4149' W/1 SPI
Set Pkr @ 4189'
Acid (4030½-4172') 2500 gals.
Swbd 52 ELO + 17 BW/8 hrs.
7-11-66 TD 4290', PBD 4248', TO Pump.
Pmpd 34 ELO + 36 BW/25 hrs & pmpd off.
7-18-66 TD 4290', PBD 4248', TO Pump.
Pmpd 4.56 BO + 24 BW/24 hrs.
Unseated Pkr @ 4189'
Pmpd 3.5 BO + 18 BW/22 hrs.

ROOSEVELT Wildcat NM
ANTWEIL, MORRIS R., #1 Captain

Sec. 8-7S-34E
Page #3

7-25-66 TD 4290', PED 4248', TO Pump.
Pmpd 3.5 BO + 16 BW/24 hrs.

8-1-66 TD 4290', PED 4248', prep to P&A.
Pmpd 3.5 BO + 17 BW/24 hrs.

8-8-66 TD 4290', PED 4248', TO Pump.
Pmpd 4.5 BO + 11.5 BW/24 hrs.

8-15-66 TD 4290', PED 4248', SI.
Pmpd 4.5 BO + 12 BW/24 hrs.

8-22-66 TD 4290', PED 4248', TO Pump.
Pmpd 4 BO + 12 BW/24 hrs.

8-29-66 TD 4290', PED 4248', TO Pump.
Pmpd 4.5 BO + 13.5 BW/24 hrs.

9-6-66 TD 4290', PED 4248', TO Pump.
Pmpd 4 BO + 16 BW/24 hrs.

9-12-66 TD 4290', PED 4248', TO Pump.
Pmpd 3½ BO + 18 BW/24 hrs.

9-19-66 TD 4290', PED 4248', TO Pump.
Pmpd 5.75 BO + 21.5 BW/24 hrs. (4030½-4172')

9-26-66 TD 4290', PED 4248', WO Pulling Unit.

10-3-66 TD 4290', PED 4248', WO Pulling Unit.

10-10-66 TD 4290', PED 4248', PLUGGED & ABANDONED.
LOG TOPS: San Andres 3330', Slaughter
3990'.