



Gammaatron

# 56682-H		COMPANY <u>PAN AMERICAN PETROLEUM CORPORATION</u>	
Permanent Datum: <u>GROUND LEVEL</u> , Elev. <u>4323</u>		WELL <u>STATE "DB" # 8</u>	
Log measured from <u>10</u> ft above perm. datum		FIELD <u>CHAVECO</u>	
Drilling measured from		COUNTRY <u>ROOSEVELT</u> STATE <u>NEW MEXICO</u>	
Location: <u>660' FSL & 1980' FWL</u> <u>SEC. 25, TWP. 7S, RGE. 33E</u>		Other Services:	
Date <u>5-28-66</u>	Run No. <u>ONE-NW</u>	Elev. <u>4333</u>	
Type Log <u>GAMMA RAY</u>	NEUTRON		
Depth-Driller <u>4430</u>			
Depth-Logger <u>4424</u>			
Bottom logged interval <u>4415</u>			
Top logged interval <u>SURF.</u>			
Type fluid in hole <u>WATER</u>			
Salinity, PPM Cl.			
Density			
Level <u>186</u>			
Max. rec. temp., deg F.			
Operating rig time			
Recorded by <u>WHEATLEY</u>			
Witnessed by			
RUN BORE-HOLE RECORD CASING RECORD			
No.	Bit	From	To
		Size <u>4 1/2"</u>	Wgt. <u>SURF.</u>
			To <u>T.D.</u>

EQUIPMENT DATA											
Gamma Ray						Neutron					
Run No.	ONE					Run No.	ONE				
Tool Model No.	500					Log Type	N-N (THERM)				
Diameter	3 1/2"					Tool Model No.	500				
Detector Model No.	5PA12					Diameter	3 1/2"				
Type	SCINT					Detector Model No.	5AL4				
Length	3"					Type	SCINT				
Distance to N. Source	104"					Length	1"				
						Source Model No.	RB-300				
General						Serial No.					
Hoist Truck No.	6212					Spacing	13.5"				
Instrument Truck No.	6212					Type	RA-BE				
Tool Serial No.	15					Strength	4.5 X 10 ⁶				

LOGGING DATA											
General			Gamma Ray				Neutron				
Run No.	From	To	Speed Ft/Min	T.C. Sec	Sens. Settings	Zero Div. L or R	G.R. Units per Log Div.	T.C. Sec.	Sens. Settings	Zero Div. L or R	N. per
	4422.5	3500	30	3	1000	0	8 API	3	164	11 L	30
	4422.5	SURF.	30-50	2	1000	0	8 API	2	164	11 L	30

Reference Literature:

Remarks:

