

30-071-10353

COUNTY ROOSEVELT FIELD Chaveroo STATE WY  
OPR PAN AMERICAN PETROLEUM CORP. MAP  
8 State "DB"  
Sec. 25, T-7-S, R-33-E CO-ORD  
660' FSL, 1980' FWL of Sec. MX 10355  
Spd 5-13-66 CLASS EL  
Cmp 5-29-66

CSG & SX - TUBING

8 5/8" 455' 250  
4 1/2" 4465' 800

LOGS EL GR RA IND HC A

TD 4465', PBD 4424'

IP San Andres Peris 4205-4341' Flwd 571 BOPD. Pot. Based on 13 1/2  
hr test of 323 BO thru 24/64" chkr., GP 200#, GP 225#, Gravity  
23., GOR 523.

Distribution limited and publication prohibited by subscribers' agreement.  
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. Cactus Drilg. Co. PROP DEPTH 4333' TYPE  
DATE

5-16-66  
5-23-66  
5-31-66

F.R. 4-21-66; Opr's Elev. 4333' KE  
PD 4375' - SA  
Contractor - Cactus Drilg. Co.  
Drilg. 2821'.  
Drilg. 4314'.  
TD 4465', PBD 4424', COMPLETE.  
Perf 4205-09', 4211-13', 4218-20', 4243-47',  
4251-53', 4255-57', 4267-70', 4274-73',  
4277-79', 4287-89', 4295-97', 4300-04',  
4307-16', 4323-25', 4327-32', 4339-41'  
W/2 SPF  
Ac (4205-4341') 2000 gals; IR 6.3 BPM  
LOG TOP: San Andres 3456'.

4333  
3456  
+8 7 1

R-9007 Inj well SA 4205-4341 w/pkr approx 4150' - Inj press limit 800  
Psi

SMD-270 Lower SA 875psi

APR 15 1986

MAY 1 1986

SEP 2 5 1984

JAN 22 1986