NEW MEXICO OIL CONSERVATION COMMUNICATION C. C. PRINCE U.S. SANTA FE FILE U.S. SANTA GIVEN SAN	NO. OF COPIES RECEIVED						
APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK AND CONTROL OF THE SERVICE STREET OF THE SERVICE SERVIC	DISTRIBUTION	NEW	MEXICO OIL CONSER	RYATION COMMISSION	۷	Form C-101	
APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK Type of Work DEEPEN DEEPEN PLUG BACK PLUG BACK APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK Type of Work PLUG BACK PLUG BACK APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK Type of Work PLUG BACK PRINT DEEPEN PLUG BACK None of Operator Name of Operator P. O. Boox 1516, Rosswall, New Mexico Location of Wall Todd Sen Andrea Location of Wall Todd Sen Andrea Todd Sen Andrea 21. Rosswall Reset Line of Sec. 32 ***** PROPOSED CASING AND CEMENT PROGRAM SIZE OF HOLE SIZE OF HOLE SIZE OF CASING WEIGHT PER FOOT SETTING DEPTH SACKS OF CEMENT 12 1/4 A 5/88 A 1/2 PROPOSED CASING AND CEMENT PROGRAM SIZE OF HOLE SIZE OF CASING WEIGHT PER FOOT SETTING DEPTH SACKS OF CEMENT 12 1/4 A 5/88 A 1/2 PLUG BACK Reset Line of Sec. 44 350 250 Circ. 17/8 A 1/2 PROPOSED CASING AND CEMENT PROGRAM SIZE OF HOLE SIZE OF HOLE SIZE OF CASING WEIGHT PER FOOT SETTING DEPTH SACKS OF CEMENT EST. TOP 12 1/4 A 5/88 A 1/2 PLUG BACK Reset Line of Sec. 44 A 5/81, 248, J-55 cag to TD and cast w/250 or reg cast, 22 Cacity. One must circ. WCC 18 hrs and pressure test to 1000 psig for 30 mills Pressure test to 1000 psig for 30 mills A Completion procedure will be determined from open hole and log analyzation value. PROPOSED CASING AND CEMENT PROGRAM SIZE OF HOLE SIZE OF MOLE SIZE OF MOLE				HOBBS OFFICE O	. 	Revised 1-1-65	5 —
APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK Total Appendix DEEPEN DEEPEN PLUG BACK TOTAL DEEPEN DEEP	-			Annald Hanna	11)CC		¬`` —
APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK 1. Type of Work 1. Type of Well 2. Type of Cype of Cype of Well 2. Type of Cype of				APRIL 11 08 P	פס הע		
APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK 7. Unit Appressed Name 8. Farm or Lecous Name							Gas Lease No.
DEEPEN DELLE DEEPEN DEE						1111111	mmm
DEEPEN DELLE DEEPEN DEE	APPLICATION	N FOR PERMIT TO	DRILL DEEDEN (OP PLUG BACK			
Type of Well State Order Order		DITTOR I ERMIT TO	DRILL, DELI LIV, C	DR I LUG DACK	-	7. Unit Agree	ement Name
Surrey DX Oil Company Address of Operation P. O. Box 1416, Rosmall, New Merico 10. Field and Pool, or Wildcot Todd San Andrees 10. Field and Pool, or Wildcot Todd San Andrees 10. Field and Pool, or Wildcot Todd San Andrees 12. County Rosswell Ro	ppu (🔻	7		-			
Name of Operator P. O. Rox 1416, Roswall, New Merico Locateo 1840 P. O. Rox 1416, Roswall, New Merico 1840 P. O. Rox 1416 P. O. Rox 1416 Roswall, New Merico 1840 P. Poposed Cepin No. Rox 1856 Roswall New Merico 1840 P. Row 1840 P. Poposed Cepin No. Rox 1856 Roswall New Merico 1840 P. Row 1840 P. Row 1840 P. Row 1840 P. Row 1840 Roswall New Merico 1840 P. Row 1840 Roswall New Merico Roswall New Mer	Type of Well	j			BACK []	8. Farm or Le	ease Name
Name of Operator P. O. Rox 1416, Roswall, New Merico Locatro 1840 P. O. Rox 1416, Roswall, New Merico 10. Field and Pool, or Wilders Todd Sen Andres 10. Field and Pool, or Wilders Todd Sen Andres 12. The Transfer of Transfer o		OTHER	,	SINGLE MUL	TIPLE ZONE	New Mexic	ce State "CC"
Address of Operator P. O. Box 1416, Roswell, New Mexico Location of Will Out Letters G Located 1840 PECT FROM THE Horth Line Rosewell 13. Prepaged Depth 19. Frametion 12. County Rosswell Rosswell Rosswell 13. Frametion 19. From The Horth Line Rosswell Rosswell Rosswell Rosswell 13. Frametion 19. From The Horth Line Rosswell Rosswe	Name of Operator					9. Well No.	
P. O. Box 1416, Roswell, New Merico Location of Well Location of Well Total San Sadres Todd San Sadres 12. County Rossevelt Rossevelt	Sunray DX 011 Com	PARY				1	
1840 PET PROM THE PET PROM TH	-				7 · F-7	10. Field and	Pool, or Wildcat
1840 FEET FROM THE REST LINE OF SEC. 32 TWP. 78 NO. 358 MAINT ROCKETTER OF THE LINE OF SEC. 32 TWP. 78 NO. 358 MAINT ROCKETTER OF THE SEC. 32 TWP. 78 NO. 358 MAINT ROCKETTER OF THE SEC. 32 TWP. 78 NO. 358 MAINT ROCKETTER OF THE SEC. 32 TWP. 78 NO. 358 MAINT ROCKETTER OF THE SEC. 32 TWP. 78 NO. 358 MAINT ROCKETTER OF THE SEC. 32 TWP. 78 NO. 358 MAINT ROCKETTER OF THE SEC. 32 TWP. 78 NO. 358 MAINT ROCKETTER OF THE SEC. 32 TWP. 78 NO. 358 MAINT ROCKETTER OF THE SEC. 32 MAINT ROCKETTER OF THE SEC. 33 MAINT ROCKETTER OF THE SEC. 33 MAINT ROCKETTER OF THE SEC. 34 MAINT ROCKETTER OF THE SEC. 35 MAINT ROCKETTER OF THE SE	P. O. Box 1416, R	pewell, New Merc	<u>lco</u>			Todd S	m Andres
19. Proposed Depth 19. Formation 20. Rotary of C.T.	Location of Well	ER LO	CATED 1840 FE	EET FROM THENOTE	hLINE	IIIIII	
19. Proposed Depth 19. Pro	1040	Pant	23	70 4			
Pervision (Show whether DF, RF, etc.) 21A. Kind & Stortus Pluy. Bond 21B. Drilling Contractor 22. Approx. Date Work will start Approved Cactus Drig Co. 4-13-66	D 1040 FEET FROM	THE STEE LIN	NE OF SEC.	MP. S RGE.	NMPM	12 County	////////////////////////////////////
19. Proposed Depth 19A. Formation 20. Retery or C.T.							(()))))))
Elevations (Show whether DF, RT, etc.) 21. Kind & Status Plug. Bond 21. Department Later Approved Cactus Drig Co. PROPOSED CASING AND CEMENT PROGRAM SIZE OF HOLE SIZE OF CASING WEIGHT PER FOOT SETTING DEPTH SACKS OF CEMENT EST. TOP 12 1/4 8 5/8 24 350 250 Circ. 7 1/8 4 1/2 9.5 4600 200 3100 1. Prepare location, move in and rig up rotary rig. 2. Drill 12 1/4" hole to approx 350' TD. Run 8 5/8", 24#, J-55 cag to TD and cant w/250 as reg cant, 2Z Caci2. Cant must circ. WOC 18 hrs and pressure test to 1000 psig for 30 mi 3. Drill 7 7/8" hele to approx 4600' TD. Run open hole logs. Run 4 1/2", 9.5#, J-55 cag TD and cast w/200 ax Incor Pox Cant. Run temp survey 8 hrs after camenting. WOC 24 hrs. Pressure test to 1000 psig for 30 min. 4. Completion procedure will be determined from open hole and log malysist VALID ABOVE SPACE DESCRIBE PROPOSED PROGRAM: IF PROPOSAL IS TO DEEPEN OR PLUE BACK, SIVE DATA ON PREFERENT PRODUCTIVE ZONE AND PROPOSED NEW PROPOSED PROPOSED NEW PROPOS			HHHHHH		HHH	1111111	HHHH
Elevetions (Show whether DF, RT, etc.) 21A. Kind & Status Plug. Bond 21B. Drilling Contractor Cactus Drig Co. PROPOSED CASING AND CEMENT PROGRAM SIZE OF HOLE SIZE OF CASING WEIGHT PER FOOT SETTING DEPTH SACKS OF CEMENT EST. TOP 12 1/4 8 5/8 24 350 250 Circ. 7 1/8 4 1/2 9.5 4 600 200 3100 1. Prepare location, move in and rig up rotary rig. 2. Drilli 12 1/4" hole to approx 350' TD. Run 8 5/8", 24#, J-55 cag to TD and cant w/250 as reg cant, 2Z Caci2. Cant must circ. WOC 18 hrs and pressure test to 1000 psig for 30 mi 3. Drilli 7 7/8" hele to approx 4600' TD. Run open hole logs. Run 4 1/2", 9.5#, J-55 cag TD and cast w/200 ax Incor Pos Cant. Run temp survey 8 hrs after camenting. WOC 24 hrs. Pressure test to 1000 psig for 30 min. 4. Completion procedure will be determined from open hole and log malysist VALID ABOVE SPACE DESCRIBE PROPOSED PROGRAM: IF PROPOSAL IS TO DEEPEN ON PLUG BACK, SIVE DATA ON PREFERENT PRODUCTIVE ZONE AND PROPOSED NEW PROPOSED PROPOSED NEW PROPOSED							
Permish Later Approved Approved Cactus Drig Co. PROPOSED CASING AND CEMENT PROGRAM SIZE OF HOLE SIZE OF CASING WEIGHT PER FOOT SETTING DEPTH SACKS OF CEMENT EST. TOP 12 1/4 8 5/8 24 350 7 7/8 4 1/2 9 .5 A600 10 200 3100 1. Prepare location, move in and rig up rotary rig. 2. Drill 12 1/4" hole to approx 350' TD. Run 8 5/8", 24%, J-55 cag to TD and cat w/250 as reg cat, 2Z CaCl2. Cat must circ. WOC 18 hrs and pressure test to 1000 psig for 30 min. 3. Drill 7 7/8" hele to approx 4600' TD. Run open hole logs. Run 4 1/2", 9.5%, J-55 cag TD and cat w/200 ax Incor Fox Cat. Run temp survey 8 hrs after cementing. WOC 24 hrs. Pressure test to 1000 psig for 30 min. 4. Completion procedure will be determined from open hole and log analysis VALUE COMMENCED. SETURG OF CASING WEIGHT PROPOSED PROGRAM: IF PROPOSAL IS TO DEEPEN OR PLUG BACK, GIVE DATA ON PRESENT ZONE AND PROPOSED NEW PROPOSED STORE SINCE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED NEW PROPOSED NEW PROPOSED NEW PROPOSED PROGRAM: IF ANY DESCRIPTION OF PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED NEW PROPOSED PROGRAM: IF ANY DESCRIPTION OF PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED NEW PROPOSED PROGRAM: IF ANY DESCRIPTION OF PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED NEW PROPOSED PROGRAM: IF ANY DESCRIPTION OF PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED NEW PROPOSED PROGRAM: IF ANY DESCRIPTION OF PROPOSED PROGRAM: IF ANY DESCRIPTION OF PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED NEW PROPOSED PROGRAM: IF ANY DESCRIPTION OF PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED PROGRAM: IF ANY DESCRIPTION OF PLUG BACK, GIVE DATA ON PRESENT PROPOSED NEW PROPOSED			<i></i>	9. Proposed Depth 1	9A. Formatio	n	20. Rotary or C.T.
PROPOSED CASING AND CEMENT PROGRAM SIZE OF HOLE SIZE OF CASING WEIGHT PER FOOT SETTING DEPTH SACKS OF CEMENT EST. TOP 12 1/4 8 5/8 24 350 250 Cire. 7 7/8 4 1/2 9.5 4600 200 3100 1. Prepare location, move in and rig up rotary rig. 2. Drill 12 1/4" hole to approx 350' TD. Run 8 5/8", 24#, J-55 cag to TD and cut w/250 as reg cut, 2Z CaCl2. Cut must circ. WOC 18 hre and pressure test to 1000 psig for 30 min. 3. Drill 7 7/8" hele to approx 4600' TD. Run open hole logs. Run 4 1/2", 9.5#, J-55 cag TD and cut w/200 ax Incor Pox Cut. Run temp survey 8 hrs after cementing. WOC 24 hrs. Pressure test to 1000 psig for 30 min. 4. Completion procedure will be determined from open hole and log analysis VALIDADE COMMENCED. 1. Pressure test to 1000 psig for 30 min. 4. Completion procedure will be determined from open hole and log analysis VALIDADE COMMENCED. 1. Pressure test to 1000 psig for 30 min. 4. Completion procedure will be determined from open hole and log analysis VALIDADE COMMENCED. 1. Pressure test to 1000 psig for 30 min. 4. Completion procedure will be determined from open hole and log analysis VALIDADE COMMENCED. 1. Pressure test to 1000 psig for 30 min. 4. Completion procedure will be determined from open hole and log analysis VALIDADE COMMENCED. 1. Pressure test to 1000 psig for 30 min. 4. Completion procedure will be determined from open hole and log analysis validade comments of the process of the preparation of the				4600	San A	ndres	Rotery
SIZE OF HOLE SIZE OF CASING WEIGHT PER FOOT SETTING DEPTH SACKS OF CEMENT EST. TOP 12 1/4 8 5/8 24 350 250 Circ. 7 7/8 4 1/2 9.5 4600 100 3100 1. Prepare location, move in and rig up rotary rig. 2. Drill 12 1/4" hole to approx 350' TD. Run 8 5/8", 24#, J-55 cag to TD and cat w/250 at reg cat, 2% CaCl2. Cat must circ. WOC 18 hrs and pressure test to 1000 paig for 30 mi 3. Drill 7 7/8" hele to approx 4600' TD. Run open hole logs. Run 4 1/2", 9.5#, J-55 cag TD and cat w/200 ax Incor Pox Cat. Run temp survey 8 hrs after cementing. WOC 24 hrs. Pressure test to 1000 paig for 30 min. 4. Completion procedure will be determined from open hole and log analysis VALID COMMENCED. COMMEN	. Elevations (Show whether DI	, RT, etc.) 21A. Kind	. & Status Plug. Bond 2:				
SIZE OF HOLE SIZE OF CASING WEIGHT PER FOOT SETTING DEPTH SACKS OF CEMENT EST. TOP 12 1/4 8 5/8 24 350 250 Circ. 7 7/8 4 1/2 9.5 4600 200 3100 1. Prepare location, move in and rig up rotary rig. 2. Drill 12 1/4" hole to approx 350' TD. Rum 8 5/8", 24#, J-55 cag to TD and cmt w/250 at reg cmt, 2Z CaCl2. Cmt must circ. WOC 18 hrs and pressure test to 1000 paig for 30 mi 3. Drill 7 7/8" hele to approx 4600' TD. Rum open hole logs. Rum 4 1/2", 9.5#, J-55 cag TD and cmt w/200 ax Incor Pox Cmt. Rum temp survey 8 hrs after cementing. WOC 24 hrs. Pressure test to 1000 paig for 30 min. 4. Completion procedure will be determined from open hole and log analysis VALD COMMAENCED. COMMAENC	Furnish Later		Approved	Cactus Dr	lg Co.	4-13-	-66
12 1/4 8 5/8 24 350 250 Cire. 7 7/8 4 1/2 9.5 4600 200 3100 1. Prepare location, move in and rig up rotary rig. 2. Drill 12 1/4" hole to approx 350' TD. Run 8 5/8", 24#, J-55 cag to TD and cut w/250 at reg cut, 2Z CaCl2. Cut must circ. WOC 18 hrs and pressure test to 1000 psig for 30 mi 3. Drill 7 7/8" hole to approx 4600' TD. Run open hole logs. Run 4 1/2", 9.5#, J-55 cag TD and cut w/200 ax Incor Pos Cut. Run temp survey 8 hrs after cementing. WOC 24 hrs. Pressure test to 1000 psig for 30 min. 4. Completion procedure will be determined from open hole and log analysis; VALID ABOVE SPACE DESCRIBE PROPOSED PROGRAM: IF PROPOSAL IS TO DEEPEN OR PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED NEW P	•	F	PROPOSED CASING AND	CEMENT PROGRAM			
12 1/4 8 5/8 24 350 250 Circ. 7 7/8 4 1/2 9.5 4600 200 3100 1. Prepare location, move in and rig up rotary rig. 2. Drill 12 1/4" hele to approx 350' TD. Run 8 5/8", 24#, J-55 csg to TD and cat w/250 spreg cat, 2Z CaCl2. Cat must circ. WOC 18 hrs and pressure test to 1000 psig for 30 mi 3. Drill 7 7/8" hele to approx 4600' TD. Run open hole logs. Run 4 1/2", 9.5#, J-55 csg TD and cat w/200 sx Incor Pos Cat. Run temp survey 8 hrs after camenting. WOC 24 hrs. Pressure test to 1000 psig for 30 min. 4. Completion procedure will be determined from open hole and log analyzing VALID COMMENCED, COMMENCED	SIZE OF HOLE	SIZE OF CASING	WEIGHT PER FOOT	SETTING DEPTH	SACKS O	F CEMENT	FST. TOP
1. Prepare location, move in and rig up rotary rig. 2. Drill 12 1/4" hole to approx 350' TD. Rum 8 5/8", 24#, J-55 csg to TD and cat w/250 st reg cat, 27 CaCl2. Cat must circ. WOC 18 hrs and pressure test to 1000 psig for 30 min. 3. Drill 7 7/8" hele to approx 4600' TD. Rum open hole logs. Rum 4 1/2", 9.5#, J-55 csg TD and cat w/200 sx Incor Pox Cat. Rum temp survey 8 hrs after comenting. WOC 24 hrs. Pressure test to 1000 psig for 30 min. 4. Completion procedure will be determined from open hole and log analysis. VALID COMMENCED. ABOVE SPACE DESCRIBE PROPOSED PROGRAM: IF PROPOSAL IS TO DEEPEN OR PLUG BACK, GIVE DATA ON PREVENT PRODUCTIVE ZONE AND PROPOSED NEW PROPOSED NEW PROPOSED TREVENTER PROGRAM, IF ANY. Table District Engineer Date April 13, 1966	12 1/4	8 5/8	1	†			†
1. Prepare location, move in and rig up rotary rig. 2. Drill 12 1/4" hole to approx 350' TD. Run 8 5/8", 24#, J-55 cag to TD and cmt w/250 at reg cmt, 2% CaCl2. Cmt must circ. WOC 18 hrs and pressure test to 1000 paig for 30 mi 3. Drill 7 7/8" hele to approx 4600' TD. Run open hole logs. Run 4 1/2", 9.5#, J-55 cag TD and cmt w/200 ax Incor Pox Cmt. Run temp survey 8 hrs after comenting. WOC 24 hrs. Pressure test to 1000 paig for 30 min. 4. Completion procedure will be determined from open hole and log analysis; VALD COMMENCED. ABOVE SPACE DESCRIBE PROPOSED PROGRAM: IF PROPOSAL IS TO DEEPEN OR PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED NEW PRESENCE COMMENCED. THE STATE OF THE BLOWGUT PREVENTER PROGRAM. IF ANY. Title District Engineer Date April 13, 1966	7 7/8		1				
2. Drill 12 1/4" hole to approx 350' TD. Run 8 5/8", 24#, J-55 cag to TD and cut w/250 at reg cut, 2% CaCl2. Cut must circ. WOC 18 hrs and pressure test to 1000 psig for 30 min. 3. Drill 7 7/8" hele to approx 4600' TD. Run open hole logs. Run 4 1/2", 9.5#, J-55 cag TD and cut w/200 ax Incor Pox Cut. Run temp survey 8 hrs after camenting. WOC 24 hrs. Pressure test to 1000 psig for 30 min. 4. Completion procedure will be determined from open hole and log analysis VALID COMMENCED, ABOVE SPACE DESCRIBE PROPOSED PROGRAM: IF PROPOSAL IS TO DEEPEN OR PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED NEW PROPOSED CHIEF TIME DISTRICT REGIMENT. Date April 13, 1966	· · · · · · · · · · · · · · · · · · ·						
ABOVE SPACE DESCRIBE PROPOSED PROGRAM: IF PROPOSAL IS TO DEEPEN OR PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED NEW PRESENT PRODUCTIVE ZONE AND PROPOSED NEW PRESENT PRODUCTIVE ZONE AND PROPOSED NEW PROPOSED CONTROL OF THE PROPOSED NEW P	 Drill 12 1/4" reg cmt, 2% Cd Drill 7 7/8" 1 TD and cmt w/2 	hole to approx aCl2. Cat must hele to approx of 200 sx Incor Pos	350' TD. Run & circ. WOC 18 h	8 5/8", 24#, J-hrs and pressur	e test t	:o 1000 pa	sig for 30 min. 5#. J-55 cag to
ABOVE SPACE DESCRIBE PROPOSED PROGRAM: IF PROPOSAL IS TO DEEPEN OR PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED NEW PRESENT PRODUCTIVE ZONE AND PROPOSED NEW PROPOSED NEW PROPOSED STREET, Title District Engineer Date April 13, 1966		• •					
ABOVE SPACE DESCRIBE PROPOSED PROGRAM: IF PROPOSAL IS TO DEEPEN OR PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED NEW PRESENT PRODUCTIVE ZONE AND PROPOSED NEW PROPOSED NEW PROPOSED STREET, Title District Engineer Date April 13, 1966	4. Completion pro	ocedure will be	determined from	n open hole and	log and	Light V	MD MD 515
ABOVE SPACE DESCRIBE PROPOSED PROGRAM: IF PROPOSAL IS TO DEEPEN OR PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED NEW PRO					**************************************	90 EATS	JENCED,
ABOVE SPACE DESCRIBE PROPOSED PROGRAM: IF PROPOSAL IS TO DEEPEN OR PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED NEW PRO					, C.	ung com	ME140
ned District Engineer Date April 13, 1966					12	5 1	6
ned District Engineer Date April 13, 1966					-voiRES		
ned District Engineer Date April 13, 1966	ABOVE SPACE DESCRIBE PI	ROPOSED PROGRAM: IF	PROPOSAL IS TO DEEPEN OF	R PLUG BACK, GIVE DATA OF	PRESENT PR	ODUCTIVE ZONE	AND PROPOSED NEW PRODU
B.F.Brawley Title District Engineer Date April 13, 1966							
2205225 Mg2Mes	``.)	zeza ot my kii	B- mim politic			
	ned B & Branding	B.F.Brewley	_ Title Distric	et Engineer		Date	11 13, 1966
	(This space for	X					

__ TITLE_

CONDITIONS OF APPROVAL, IF ANY: