

COUNTY ROOSEVELT FIELD Chaveroo STATE NM
 OPR CHAMPLIN PETROLEUM CO. MAP
14 Lauck-Federal
Sec. 29, T-7-S, R-33-E CO-ORD
660' FSL, 660' FWL of Sec. MX 10561
Spd 4-23-66 CLASS EL
Cmp 5-14-66

CSG & SX - TUBING

8 5/8" 360' 325
 4 1/2" 4445' 325

LOGS EL GR RA IND HC A

FORMATION	DATUM	FORMATION	DATUM

TD 4445'

IP San Andres Perfs 4200-4402' Swld 87 BOPD + 86 BW. Pot.
 Based on 24 hr test, gravity 24.6, GOR TSTM.

Distribution limited and publication prohibited by subscribers' agreement.
 Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT.
 DATE

PROP DEPTH 4500' TYPE RT

F.R. 4-28-66; Cpr's Elev. 4440' DF
 PD 4500' - SA
 5-2-66 Drlg. 4243' lm.
 5-9-66 TD 4445', WO Pump.
 Perf @ 4200', 4222', 4264', 4275', 4290',
 4309', 4325', 4344', 4394', 4402' W/2 SPI
 Ac (4200-4402') 500 gals.
 Frac (4200-4402') 50,000 gals wtr +
 40,000# sd.
 5-23-66 TD 4445', pmpg load.
 5-31-66 TD 4445', COMPLETE.
 LOG TOPS: Anhydrite 1775', Yates 2306',
 Queen 2980', San Andres 3533'.

4440
 3533
 17.
 76
 987