

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions reverse side)Form approved.
Budget Bureau No. 42-R1424.
5. LEASE DESIGNATION AND SERIAL NO.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR Champlin Petroleum Company	8. FARM OR LEASE NAME Payroll-Federal
3. ADDRESS OF OPERATOR P. O. Box 1797, Midland, Texas	9. WELL NO. 3
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 660' FSL & 1980' FSL, Section 30, T-7-S, R-33-E State Unit-I	10. FIELD AND POOL, OR WILDCAT Undesignated
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.) 4429' GR
	11. SEC., T., R., E., OR BLK. AND SURVEY OR AREA Sec. 30, T-7-S, R-33-E
	12. COUNTY OR PARISH Rockwall
	13. STATE Texas

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF	☐	PULL OR ALTER CASING	☐
FRACTURE TREAT	☐	MULTIPLE COMPLETE	☐
SHOOT OR ACIDIZE	☐	ABANDON*	☐
REPAIR WELL	☐	CHANGE PLANS	☐
(Other)	☐		☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF	☒	REPAIRING WELL	☐
FRACTURE TREATMENT	☒	ALTERING CASING	☐
SHOOTING OR ACIDIZING	☒	ABANDONMENT*	☐
(Other)	☐		☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled 7-7/8" hole to TD 4442'. Set 4-1/2", 9.5# Limited Service Casing 4442'. Cemented with 325 sacks Incoor Pozmix plus 2% Gel and 8# salt per sack. Plug down @ 7:15 P.M. 5-13-66. Pump plug down with 500 gal. MHA acid. Tested casing to 2000# with water for 30 minutes. Test okay @ 8:00 P.M. 5-14-66. Perf 2 - 3/8" jets per interval @ 4183, 4209, 4250, 4262, 4281, 4293, 4324, 4371, & 4387'; one each interval @ 4177 & 4331'. Fraced same perf. with 50,000 gal. Gelled Formation water and 40,000# 20-40 sand, using ball sealers. Swabbed load back. 24 hr. Swab Test 5-21-66, 75 bbls. oil and 290 bbls. water.

Run rods & bottom hole pump for completion.

18. I hereby certify that the foregoing is true and correct

SIGNED H. F. Brown H. F. Brown TITLE District Superintendent DATE 5-24-66

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____

DATE

APPROVED

MAY 25 1966

*See Instructions on Reverse Side

J. L. GORDON
ACTING DISTRICT ENGINEER

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.