

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPI TE*
(Other instructions: re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.
Federal # 0108997

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Farrell Federal

9. WELL NO.
4

10. FIELD AND POOL, OR WILDCAT
Undesignated

11. SEC., T., R., & GR. BLK. AND
SURVEY OR AREA

Sec. 30, T-7-S, R-33-E

12. COUNTY OR PARISH
Reconville

13. STATE
New Mexico

1. OIL WELL ☒ GAS WELL ☐ OTHER

2. NAME OF OPERATOR
Champlin Petroleum Company **Warren American Oil Company**

3. ADDRESS OF OPERATOR
P. O. Box 1797, Midland, Texas

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface
**660' FSL & 660' FSL of Section 30, T-7-S, R-33-E
State Unit-D**

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled 7-7/8" hole to TD 4450'. Set 4-1/2" 9.5# Limited Service Casing @ 4450'. Cemented with 325 sacks Incoor Poemix plus 2% Gel & 8% Salt per sack. Pumped plug down with 500 gallons 10% Acetic Acid @ 4:15 P.M. on 5-23-66. Tested pumping and blow-out preventers for 30 minutes with water to 2000#. Tested okay @ 6:00 P.M. 5-24-66. Perforated two 3/8" jets per interval @ 4200, 4231, 4259, 4331, 4338, & 4393; and one 3/8" jet per interval @ 4183, 4214, 4267, 4279, 4316, 4341, 4377, & 4399'. Fraced same perforations with 50,000 gallons gelled formation water and 40,000# 20-40 sand. Swabbed load back. For completion set fishing @ 4416' and seating nipple @ 4376'. Ran rods and bottom hole pump. 24 hour pumping test on 6-21-66 - 60 bbls. oil and 60 bbls. water.

18. I hereby certify that the foregoing is true and correct

SIGNED H. N. Brown H. N. Brown

District Superintendent

DATE 6-21-66

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

APPROVED

JUN 22 1966

*See Instructions on Reverse Side

J. L. GORDON
ACTING DISTRICT ENGINEER

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 7: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1963-O-485229

697-581