

COUNTY	ROOSEVELT	FIELD	Wildcat	STATE	NM
OPR	ANTWEIL, MORRIS R.				MAP
	1 Scott				
	Sec. 2, T-7-S, R-34-E				CO-ORD
	1980' FSL, 660' FEL of Sec.				MX 10564
	Spd 4-23-66				
	Cmp 9-28-66				
	FORMATION		DATUM		
CSG & SX - TUBING					
8 5/8" 406' 300					
4 1/2" 4350' 325					
LOGS EL GR RA IND HC A					
	TD 4350'				
PLUGGED & ABANDONED					

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. Leatherwood Drig. Co. PROP DEPTH 4500' TYPE
DATE

F.R. 4-28-66
PD 4500' - SA
Contractor - Leatherwood Drig. Co.
5-2-66 Drig. 4174' lm.
5-9-66 TD 4350', prep to perf.
Cored 4190-4252', rec 62' dolo & anhy.,
w/scatt shows.
Cored 4252-4318', rec 66' same.
5-16-66 TD 4350', prep to Ac.
Perf @ 4290', 4296', 4298', 4306', 4308',
W/1 SPI
Acid (4290-4308') 2500 gals.
Swbd 77 BF/9 hrs (45% wtr, w/sli show gas)
Perf @ 4094', 4124', 4202', 4204', 4208',
4212', 4218', 4222', 4224' W/1 SPI
5-23-66 TD 4350', swbg.
Set BP @ 4265'.

5-23-66 Continued
Acid (4094-4224') 2500 gals.
Swbd 26.5 BF/9 hrs (20% oil, 80% Acid
& Form Wtr) (4094-4224')

5-31-66 TD 4350', SI.
6-6-66 TD 4350', SI.
6-13-66 TD 4350', swbg.
Frac (4094-4224') 40,000 gals wtr +
40,000# sd.
Swbd 150 BLW/29 hrs, w/good show gas &
sli show oil. (4094-4224')

6-20-66 TD 4350', tstg on pump.
Pmpd 2 BO + 52 BLW/24 hrs.
6-27-66 TD 4350', TO Pump.
Pmpd 16 BO + 51 B Salt Wtr/24 hrs (4094-4224')

7-5-66 TD 4350', TO Pump.
Pmpd 5 BO + 21 BW/23 hrs (4094-4224')

7-11-66 TD 4350', TO Pump.
7-12-66 TD 4350', prep Acid.
Pulled BP @ 4265'

7-18-66 TD 4350', TO Pump.
Acid (4094-4308') 5000 gals.
Pmpd 21 BLO + 22 BAW/24 hrs (4094-4308')

7-25-66 TD 4350', TO Pump.
Pmpd 11 BNO + 30 BW/24 hrs (4094-4308')

8-1-66 TD 4350', TO Pump.
Pmpd 11.6 BO + 30 B Salt Wtr/24 hrs.

8-8-66 TD 4350', SD Pump Repairs.
Pmpd 5.7 BO + 22 B Salt Wtr/24 hrs
(4094-4308')

ROOSEVELT Wildcat
ANTWEIL, MORRIS R., #1 Scott

NM

Sec. 2-7S-34E

Page #3

8-15-66 TD 4350', Tstg.
 Set Pkr @ 4260'
 Pmpd 2 BO + 12 BW/6½ hrs (4094-4224')
8-22-66 TD 4350', Tstg.
 Pmpd 10 BO + 9 BW/24 hrs.
8-29-66 TD 4350', TO Pump.
 Pmpd 10 BO + 21 BW/24 hrs.
9-6-66 TD 4350', TO Pump.
 Pmpd 5 BO + 15 BW/24 hrs. (4094-4224')
9-12-66 TD 4350', TO Pump.
 Treated (4094-4224') 60 bbls hot oil
 Pmpd 30 BLO + 10 BW/22 hrs (4094-4224')
9-19-66 TD 4350', TO Pump.
 Pmpd 4 BO + 9 BW/no time.

9-26-66 TD 4350', TO Pump.
 Pmpd 7 BO + 20 BW/24 hrs.
10-3-66 TD 4350', PLUGGED & ABANDONED.
 Pmpd 5 BO + 21 BW/24 hrs (4094-4224')
 LOG TOP: San Andres 3420' (+ 870')