

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on reverse side)Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐		5. LEASE DESIGNATION AND SERIAL NO. NM-0164650	
2. NAME OF OPERATOR San American Petroleum Corp.		6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
3. ADDRESS OF OPERATOR Box 68, Hobbs NM 88240		7. UNIT AGREEMENT NAME	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1980 FNL x 2310' FEL, Sec. 19 (Unit G, SW 1/4 NE 1/4)		8. FARM OR LEASE NAME JOYCE WOLF FEDERAL	
14. PERMIT NO.		9. WELL NO. 1	
15. ELEVATIONS (Show whether DF, ST, GR, etc.) 4328' RDB		10. FIELD AND POOL, OR WILDCAT CHAUEROO SAN ANDRES	
16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA 19-7-34 NMPM	
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)		12. COUNTY OR PARISH ROOSEVELT	
		13. STATE N.M.	

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT ON:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

TD 4355. On 6-8-66. 4 1/2" OD 9.5" J-55 casing was set at 4355' w/ 5005 x 12% bel Incon + 300 sq inch. Tested casing w/ 2000 psi for 30 minutes. Test O.K. Evaluated as follows: Perf 4268-98 w/ 2500' F. Acidized w/ 2000 gal. Frac w/ 30,000 gal oil, 40,500# sand, 3000# glass beads. Evaluated. Covered w/ sand. Perforated 4108-23, 4127-4214 w/ 2500' F. Acidized w/ 2000 gal. Frac w/ 30,000 gal oil, 40,500# sand, 3000# glass beads. Evaluated.

4268-98 - PT 7280 x 48W 24th - 6-25-66

4108-4298 TML 9780 x 28W 24th. 7-11-66

TD 4355

PAD 4320

TPAT 4108

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

DATE

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

APPROVED
JUL 18 1966

DISTRICT ENGINEER

*See Instructions on Reverse Side

4- USGS 16
1- N250
1- Susp
1- R2y