

COUNTY ROOSEVELT		FIELD Wildcat		STATE NM	
OPR CACTUS DRILLING CORPORATION				MAP	
1 Kewanee-State					
Sec. 9, T-7-S, R-35-E				CO-ORD	
1980' FNL, 660' FEL of Sec.				MX 10579	
Spd 6-2-66				CLASS	
Cmp 9-12-66				E	
		FORMATION	DATUM	FORMATION	DATUM
CSG & SX - TUBING					
8 5/8"	362'	200			
4 1/2"	4370'	150			
LOGS EL GR RA IND HC A					
		TD 4375'			
TEMPORARILY ABANDONED					

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. Cactus Drlg. Co.	PROP DEPTH 4500'	TYPE
DATE		

F.R. 5-26-66; Opr's Elev. 4241' KB
PD 4500' - SA
Contractor - Cactus Drlg. Co.
6-6-66 Drlg. 3720'.
6-13-66 TD 4375', circ., prep to run 4 1/2" casing.
Cored 4210-32', rec 18' being:
9' tight dolo; 9' dolo., w/scatt fracs.
Cored 4232-68', rec 36' being:
3' dolo., w/scatt fracs., poor PPP; 3'
tight dolo; 19' dolo., w/scatt PPP &
fracs; 11' tight dolo.
6-17-66 TD 4375', prep to Acid.
Perf 4342-47' W/2 SPF
6-27-66 TD 4375', PBD 4334', SI.
Acid (4342-47') 500 gals.
Swbd salty sul wtr (4342-47')

6-27-66 Cont.
Set BP @ 4334'
Perf @ 4195', 4199', 4223', 4229', 4235',
4240', 4247', 4253', 4259', 4264' W/1 SPI
Acid (4195-4264') 1500 gals.
Flwd 3 BOPH for 8 hrs. (4195-4264')
7-5-66 TD 4375', PBD 4334', tstg.
7-11-66 TD 4375', PBD 4334', tstg.
7-18-66 TD 4375', PBD 4334', tstg.
Flwd 11 BO + 140 BW/24 hrs thru 18/64"
chk. (4195-4264')
7-25-66 TD 4375', Prep to run tracer.
Flwd 13 BO + 130 BW/24 hrs thru 18/64"
chk., TP 325#. (4195-4264')
8-1-66 TD 4375', PBD 4334', swbg.
Squeezed perfs 4195-4264'

Perf @ 4320'
Squeezed perf @ 4320'
Perf @ 4244', 4248', 4251', 4253', 4259',
4263' W/1 SPI
Acid (4244-63') 1000 gals.
8-8-66 TD 4375', PBD 4240', tstg.
Swbd 11BFPH (10% oil, 90% wtr) (4244-63')
Squeezed perfs 4244-63'
Drld out to 4240'
Perf @ 4223', 4228', 4233', 4235', 4238'
W/1 SPI
Acid (4223-38') 1000 gals.
Flwd 750 MCFGPD + 5 BW/24 hrs (4223-38')
8-15-66 TD 4375', PBD 4240', tstg.
8-22-66 TD 4375', PBD 4257', SI.
Set Pkr @ 4210'
Swbd dry (4223-38')
Drld out to 4257'

8-22-66 Cont.
Perf @ 4248', 4252', 4253' W/1 SPI
Set Pkr @ 4244'
Acid (4248-53') 1000 gals.
Swbd 7-8 B Salt Wtr PH (4248-53')
8-29-66 TD 4375', PBD 4257', tstg (no gauge)
9-6-66 TD 4375', PBD 4257', tstg.
Flwd 500 MCFGPD on 16/64" chk., + unest.
amount of wtr.
9-12-66 TD 4375', PBD 4257', TEMPORARILY ABANDONED.
LOG TOPS: Yates 2335', San Andres 3450',
Pi Zone 3970'.