OPR HUMBLE OIL & REFG. CO.	<u> </u>		MA	P
<u> </u>	····			
<u>Sec. 30, T-7-S, R-33-E</u>		CO-ORD		
660' FNL, 1980' FWL of Sec.		MX 10616		
· · · · · · · · · · · · · · · · · · ·	····	CLASS	E	L
	FORMATION	DATUM	FORMATION	DATU
CSG & SX - TUBING				
Γ				
		<u> </u>		

____^

. -

	Distribution limited and publication prohibited by subscribers' agreement. Reproduction rights reserved by Williams & Lee Scouting Service, Inc.		
CONT. ATE	<u>ргор дертн 4500'</u>	TYPE	

	F.R. 8-4-66
	PD 4500' - SA
8-11-66	DISREGARD FIRST REPORT DATED 8-4-66, reported
	in error. DELETE REFERENCE #MX 10616.

OPR HOMBLE OIL & REFG. (IOMPARY		MA	P
1 Andrews-Faderal				
Sec. 30, 7-7-5, R-33	3-E		CO-OF	
660' FNL, 1980' FWL				584
Spd 6-17-66		CLASS		
Cmp 8~13-66	FORMATION	DATUM	FORMATION	UM
CSG & SX - TUBING				
8 5/8" 211' 125				
4 1/2" 4400' 500				
LOGS EL GR RA IND HC A		<u> </u>		
	TD 4400', P	KD 43641		

1 · · · · · · ·

	F.R. 6-9-66
	PD 4500' · Sat Andres
8-11-66	DISREGARD FIRST REPORT DATED 8-4-56, reported
	in error. Delete Reference #MX 10616.
8-8-66	TD 4400', PBD 4364', WO Electricity.
	Perf @ 4148', 4152', 4159', 4162', 4164',
	4171', 4214', 4219', 4227', 4233', 4237',
	4240', 4250', 4252', 4264', 4267', 4269',
	4272' W/1 SPI
	Acid (4148~4272°) 2250 gals.
	Pmpd 16 BO + 49 BLW/24 hrs.
	Frac (4148-4272) 40,000 gals wtr + 40,000# sd.
	Swbd 15 BO + 32 BLW/7 hrs (-414 BLW)
8-15-66	TD 4400', PBD 4364', tsrg on pump.
	Pmpd 35 BO + 45 BLW/24 hrs.
8-22-66	'TD 4400', PED 4364', tstg on pump.
	Pmpd 9 B0 + 9 BLW/18 hrs.

ROOSEVELT Chaverco NM Sec. 30-7S-33E HUMBLE OIL & REFG. CC., #1 Andrews-Federal Page #2 8-29-66 TD 4400', PBD 4364', WO Potential. Pmpd 18 BO + 10 BLW/24 hrs. TD 4400', PBD 4364', COMFLETE. LOG TOP: San Andres 3430'.

6-66