	if h. Cl. Calls. Callward P. C. BOX 1930	ł
(December 1989) DEPARTMEN	TED STATES HOBBS, NEW MEXICO 882 TOF THE INTERIOR LAND MANAGEMENT	FORM APPROVED Budget Bureau No 1004-0135 Expires: September 30, 1990 5 Lease Designation and Serial No.
		LC-060978
Do not use this form for proposals to dr	AND REPORTS ON WELLS fill or to deepen or reentry to a different reservoir R PERMIT—" for such proposals	6 If Indiari, Allottee or Tribe Name
SUBMIT IN TRIPLICATE		7. If Unit or CA, Agreement Designation
1. Type of Well           X         Oil         Gas           Well         Well         Other		MILNESAND (SAT.) UNIT 8 Well Narne and No.
2. Name of Operator XERIC OIL & GAS COMPANY		213 9. API Wel No.
3. Address and Telephone No.		30-041-16587
P.O. BOX 51311, MIDLAND, TEXAS 79710 (915)683-3171		10. Field and Pool, or Exploratory Area
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)		MILNESAND (SAN ANDRES 11. County or Parish, State
860FNL,660FWL,S20, T8S,F	R35E Umt B	Roosevelt
2 CHECK APPROPRIATE BOX	(S) TO INDICATE NATURE OF NOTICE, REPO	ORT, OR CTHER DATA
TYPE OF SUBMISSION	TYPE OF ACTIO	N
Notice of Intent	Abundonmen!	Change of Plans New Construction
Subsequent Report	Plugging Back Casing Repair	Non-Routine Fracturing Water Shut-Off
Final Abandonment Notice	Altering Casing	Conversion to Injection Integrity Test s of multiple completion on Well Completion or
	Recompletion Repor	n and Log form )
give subsurface locations and measured and true series Cast iron bridge plug is s	-	
14. Thereby certify that the foregoing is the and correct	THE OPERATIONS MANAGER	APPR(D0429-92 7
Signed Them Alafford	THE OF ERATIONS MANAGER	PETER W. CHESTED
(This space for Federa: or State office yse)		NORA
Approved by Conditions of approval. if any. See allae	ched slept	

Title 18 U.S.C. Section 1001 makes it a crime for any person knowingly and willfully in any etains department or ages in the BUREAU OF CAND MANAGE MENT or representations as to any matter within its jurisdiction

## Additional Stipulations for Casing Integrity Test

1. The cast iron bridge plug shall be set within 100 ft. of the upper most perforations or casing shoe if completed open hole.

2. Also notify the New Mexico Oil Conservation Division (NMOCD) prior to test.