

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPT
(Other descriptions
reverse side)

FE-
10-

Form Approved
Budget Control No. 42-21424

5. LEASE DESIGNATION AND SERIAL NO.

LC-060978

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Jacobs Federal

9. WELL NO.

13

10. FIELD AND POOL, OR WILDCAT

Milnesand (San Andres)

11. SEC., T., R., M., OR BLM. AND
SURVEY OR AREA

20 SS 35E

12. COUNTY OR PARISH 13. STATE

Roosevelt New Mexico

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Mobil Oil Corporation (Formerly Socony Mobil Oil Co., Inc.)

3. ADDRESS OF OPERATOR

P. O. Box 633, Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)

At surface

860' FNL & 660' FWL of Sec. 20, Unit "D"

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4210 GL

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING ~~SHOOTING~~ ☒

(Other) Perforating

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

June 30, 1966. Total Depth 4820, PBD 4782. San Andres (4599-4723) OA. Lane Wells Co. perf additional holes in 4 1/2" casing w/San Andres at 4623-44-50-65-69, 1 ft. sh/interval. Lane Wells set Halliburton SVDC Ret at 4680. Setting tool would not shear off. Pulled line out of rope socket. Ran BOS on 2" tbg. Recovered setting tool. Ran stinger on 2" tbg to Ret. at 4680. Then Halliburton sq. perfs 4690-4723 w/75 sax Trinity Inferno Neat. Communicated w/upper perfs. TP 1200 - CP 1300 w/stinger at 4678. Reversed out 10 sax. Pulled tubing and stinger.

18. I hereby certify that the foregoing is true and correct

SIGNED

T. A. Payne

TITLE

Authorized Agent

DATE

7-11-66

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

APPROVED

JUL 18 1966

A. R. BROWN
DISTRICT ENGINEER