

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION C. C.

JUL 25 9 45 AM '66

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>	
5. State Oil & Gas Lease No. OG-929	
7. Unit Agreement Name	
8. Farm or Lease Name Section 36	
9. Well No. 1	
10. Field and Pool, or Wildcat Undesignated	
12. County Roosevelt	

**SUNDRY NOTICES AND REPORTS ON WELLS**  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	2. Name of Operator Marathon Oil Company
3. Address of Operator P. O. Box 220, Hobbs, New Mexico	4. Location of Well UNIT LETTER <u>B</u> <u>660</u> FEET FROM THE <u>North</u> LINE AND <u>2310</u> FEET FROM THE <u>East</u> LINE, SECTION <u>36</u> TOWNSHIP <u>7S</u> RANGE <u>33E</u> NMPM.
15. Elevation (Show whether DF, RT, GR, etc.) unknown	

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/> TEMPORARILY ABANDON <input type="checkbox"/> PULL OR ALTER CASING <input type="checkbox"/> OTHER <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/> COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/> CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Well was spudded July 19, 1966 and drilled to 350'. Ran and set 11 jts. 8-5/8", 24#, 8 R thd, J-55, ST&C new casing from 12.00' below KB to 347.78' with setting depth including Baker guide shoe 1.08'. Casing cemented with 275 sacks Class A cement with 2% calcium chloride. Bottom 3 jts. casing Baker locked and bottom jt. has centralizers. Cement circulated to surface. W.O.C. 20 hrs. and tested with 800# for 30 min., holding O.K.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>[Signature]</u>	TITLE <u>Area Superintendent</u>	DATE <u>July 21, 1966</u>
APPROVED BY _____	TITLE _____	DATE _____

CONDITIONS OF APPROVAL, IF ANY: