

COUNTY	ROOSEVELT	FIELD	Wildcat	STATE	NM
OPR	AZTEC OIL & GAS COMPANY				MAP
	1 Federal "SA"				
	Sec. 24, T-7-S, R-37-E				CO-ORD
	1980' FNL, 1980' FEL of Sec.				MX 10598
	Spd 6-20-66		CLASS	EL	
	Cmp 8-17-66		FORMATION	DATUM	FORMATION DATUM
CSG & SX - TUBING					
	8 5/8"	365'	200		
	4 1/2"	4798'	150		
LOGS EL GR RA IND HC A					
			TD 4820'		
TEMPORARILY ABANDONED					

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT.	PROP DEPTH	5200'	TYPE
DATE			

F.R. 6-23-66; Opr's Elev. 4044' DF
 PD 5200' - SA
 6-27-66 Drlg. 4065'.
 7-5-66 TD 4820', SDO.
 DST 4300-4443', open 30 mins,
 Rec 5' DM,
 30 min ISIP 555#, FP 103-103#,
 30 min FSIP 284#.
 DST 4605-95', open 35 mins,
 rec 20' DM,
 30 min ISIP 1165#, FP 76-76#,
 30 min FSIP 511#.
 DST 4732-95', open 30 mins,
 rec 180' DM + 630' Salty Sul Wtr,
 1 hr ISIP 1689#, FP 76-497#,
 1 hr FSIP 1638#.

7-11-66 TD 4820', PBD 4764', SI for BHP.
Perf @ 4618', 4626', 4628' W/1 SPI
Acid (4618-28') 2000 gals.
Perf @ 4670', 4674', 4676', 4681', 4686',
4688', 4690' W/1 SPI
Acid (4670-90') 2000 gals.
Had Communications
Perf @ 4716', 4722', 4724', 4728' W/1 SPI
Acid (4716-28') 2000 gals.
Swbd 12 BAW/7 hrs (4618-4728')
7-18-66 TD 4820', PBD 4764', SDO.
Frac (4618-4728') 20,000 gals wtr + 20,000# sd.
Swbd 50 BLW/7 hrs & swbd dry.
7-25-66 TD 4820', PBD 4764', SDO.
Swbd 40 BLW/6 hrs.
8-1-66 TD 4820', PBD 4764', SDO.

8-8-66 TD 4820', PBD 4764', SDO.
8-15-66 TD 4820', PBD 4764', SDO.
8-22-66 TD 4820', PBD 4764', TEMPORARILY ABANDONED.
LOG TOPS: Yates 2634', San Andres 3820'.