

COUNTY	ROOSEVELT		FIELD	Chaveroo	STATE	NM
OPR	KERMIT OIL COMPANY					
	1 State					
	Sec. 25, T-7-S, R-33-E					
	1980' FNL, 660' FEL of Sec.					
	Spd 7-18-66					
	Cmp 7-30-66					
			CLASS		EL	
			FORMATION	DATUM	FORMATION	
CSG & SX - TUBING						
7 5/8"	1826'	350				
4 1/2"	4420'	325				
LOGS	EL	GR	RA	*IND	HC	A
	TD 4420', PBD 4386'					
IP San Andres Perfs 4196-4308' Flwd 298 BOPD + 33 BW. Pot.						
Based on 24 hr test thru 24/64" chk., TP 200#, Gravity 26.,						
GOR 996.						

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. Brown Drlg. Co. PROP DEPTH 4600' TYPE
DATE

F.R. 7-21-66
PD 4600' - SA
Contractor - Brown Drlg. Co.
7-25-66 Drlg. 4230' lm.
8-1-66 TD 4420', PBD 4386', tstg.
Perf @ 4196', 4197', 4251', 4259', 4262',
4275', 4281', 4287', 4296', 4303', 4308'
W/1 SPI
Acid (4196-4308') 2000 gals.
Flwd 13½ BO per hr thru 24/64" chk., TP 200#.
8-8-66 TD 4420', PBD 4386', WO Potential.
8-15-66 TD 4420', PBD 4386', COMPLETE.
LOG TOPS: Anhydrite 1880', Top Salt 1950',
Base Salt 2230', Yates 2275', Seven Rivers
2386', San Andres 3457'.

R-9007 Inj. SA 4196-4308 w/ptv approx 4093 - Inj. pressure limit 800 Psi

