

TP San Andres Perfs 4115-4259' Flwd 234 BOPD. Pct. Based on 12 hr test of 127 BO thru 32/64" chlk., TP 200#, CP 500#, GOR 700, Est.

CONT.	PROP DEPTH	4500'	TYPE
DATE			

E.R. 7-21-66
PD 4500' - SA
8-1-66 Drlg. 2432'.
8-9-66 TD 4410', WC Completion Unit.
8-15-66 TD 4410', PBD 4387', swbg load.
Perf @ 4115', 4120', 4127', 4133', 4142',
4146', 4151', 4177', 4183', 4192', 4193',
4195', 4222', 4229', 4236', 4242', 4250',
4255', 4259' W/1 SPT
Acid (4115-4259') 2500 gals.
Frac (4115-4259') 30,000 gals oil + 44,000#
sd. (-771 BLO)
8-22-66 TD 4410', PBD 4387', swbg load.
Swbd & Flwd 70 BLO/12 hrs. (-25 BLO)
8-29-66 TD 4410', PED 4387', WC Per.
Flwd 234 BO/24 hrs thru 32/64" chk., TP
200#, CP 500#.

ROOSEVELT Chaveroo NM
KERR-McGEE CORPORATION, #5 State "G"

Sec. 19-7S-34E
Page #2

9-6-66

TD 4410', PED 4387', COMPLETE.

LOG TOPS: Yates 2262, San Andres 3403'.