

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen of pits, ditches, or different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

5. LEASE DESIGNATION AND SERIAL NO.

ML-001217

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

9. FARM OR LEASE NAME

10. FIELD AND POOL, OR WILDCAT

11. SEC., T., R., OR BLK. AND
SURVEY OR AREA

12. COUNTY, STATE, AND ZIP CODE

1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

3. **Delport Oil Corporation**4. **1171 First National Bank Bldg., Dallas, Texas**
See also space 17 below.)
At surface

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

16. **Corrected Elevation 1112 KB** **Roosevelt** **New Mexico**
Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Well was drilled to 4500' T. D. - Core No. 1 - 4323-82 Rec. 59' dolo bleeding oil & water 4368-82. Core No. 2 4382-4405 Rec. 23' dolo bleeding oil & water 4382-4397.h. Dst 4345-4405 weak blow. Recovered 30' drilling mud no shows. Ran logs and plugged Sept. 29, 1966 as follows:

Filled hole with heavy mud

Spot 30 sacks cement at T. D. 4500'

Spot 30 sacks cement at base of salt 2450'

Spot 30 sacks cement at top of salt 2250'

Spot 30 sacks cement in & out of base of surface pipe 368'

10 sacks cement in top of surface pipe

Erect 4" marker with Company name and well location and name. All cement spotted through the drill pipe by Halliburton.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

DATE

(This space for Federal or State office use)

APPROVED BY

TITLE

APPROVED

CONDITIONS OF APPROVAL, IF ANY:

DEC 7 1966

*See Instructions on Reverse Side

J. L. GORDON
ACQUISITION ENGINEER

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1963-O-685229

967-951

DRELLING LOG

0-320	Sand & Galls
320 - 2090	Sh. rd. sh. shale
2090 - 2245	shale & rd shale
2245 - 2460	Salt
2460 - 2570	sh. rd. sh. shale
2570 - 3140	Anhyd. rd. sh. & sh
3140 - 48	Anhydrite
3148 - 3485	rd. sh. Anhyd
3485 - 3578	Anhyd. Limestone
3578 - 4500	Shale & sh. shale

RPS

Top salt	2258
N/Salt	2460
Yates	2570
Seven Rivers	2569
Queen	3146
Panorama	3238
San Andres	3578
P1 Marker	4109
TD	4500