

COUNTY ROOSEVELL		FIELD Chavero		STATE NM	
OPR SHELL OIL COMPANY				MAP	
3 CVE State					
Sec. 31, T-7-S. R-33-E				CO-ORD	
1980' FSL, 1980' TEL of Sec.				MX 10623	
Spd 8-31-66		CLASS			
Cmp 10-1-66		FORMATION	DATUM	FORMATION	DATUM
CSG & SX - TUBING					
8 5/8" 360' 275					
5 1/2" 4424' 650					
LOGS EL GR RA IND HC A					
		TD 4425', PED 4392'			

IP San Andres Perfs 4231-99' Pmpd 66 BOFD + 57 BW. Pot. Based on 22 hr test of 60 BO + 32 BW, gravity 23.8, GOR TSTM.

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT.	PROP DEPTH 4450'	TYPE
DATE		

F.R. 8-25-66
PD 4450' - SA
9-6-66 Drlg. 3972'.
9-12-66 TD 4425', WOC.
9-19-66 TD 4425', PED 4392', pmpg load.
Perf @ 4231', 4233', 4238', 4262', 4270',
4272', 4275', 4277', 4280', 4286', 4288',
4291', 4294', 4297', 4299' W/1 SPI
Acid (4231-99') 1500 gals.
Frac (4231-99') 20,000 gals oil + 20,000# sd.
Pmpd 105 BLO + 18 BW/21 hrs.
9-26-66 TD 4425', PED 4392', pmpg load.
Pmpd 15 BLO + 140 BW/24 hrs. (-129 BLO)
10-3-66 TD 4425', PED 4392', TO Pump.
Pmpd 120 BF (60% wtr) in 24 hrs
10-10-66 TD 4425', PED 4392', COMPLETE.
LOG TOPS: Yates 2308', San Andres 3480',
San Andres Marker 4036'.