

COUNTY BOOSEBURY		FIELD Chatham		STATE NY	
OPR SOUTHERN PETROLEUM EXPLORATION, INC.				MAP	
6 State "F"					
Sec. 26, T-5-S, R-10-E				CO-ORD	
10483' - 10800' FWL of Sec.				N. 10527'	
Std 9-22-66		CLASS			
Comp 11-7-66		[REDACTED]			
		FORMATION	DATUM	FORMATION	DATUM
CSG & SX - TUBING					
8 5/8" 294' 100					
4 1/2" 4462' 35					
LOGS EL GR RA IND HC A					
		10-11-66	10-11-66		

1P San Andres Perfs 4113-4323' Prod 7" 5000 + 85 FWL Est.
Based on 24 hr test, gravity 21%, POR 60%.

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT.	PROP DEPTH 4500'	TYPE
DATE		

P.R. 9-22-66: 2nd's Clay. 4114' - 4115'
10-12-66 TO 4480', FRO 4471', swbg.
Perf @ 4113', 4229', 4281', 4314', 4350',
4381', 4393', 4394', 4395', 4318', 4322',
4325' W/1 SPH
Acid (4213-4315') 1000 gals.
Frac (4113-4323') 10,000 gals oil + 25,000# sd.
10-24-66 TO 4481', FRO 4471', swbg load.
Swbd 39 BLD + 10 BW 24 hrs.
10-31-66 TO 4480', FRO 4471', 80 Pump Repairs.
Empd 40 BLD + 38 BW 24 hrs.
11-7-66 TO 4481', FRO 4471', COMPLETES.
LOG TOPS: Ashhydrite 1860', Lates 1813',
Queen 2930', San Andres 3496'.