

EP 162#, Gravity 25.

DATE _____

11-7-66 AMEND FOOTAGE: Formerly 2314' ESL, 660' ESL
of Sec.

COUNTY	FOOSEE		FIELD	C-241110		STATE	TX
OPR	TENNECO OIL COMPANY					MAP	
	3 State "T"						
	Sec. 30, T-7-S, R-34-E					CO-ORD	
	2314' ESL, 668' ETL of 100'					MX 10635	
	Spd 10-2-66					CLASS	EL
	Cmp 10-15-66					FORMATION	DATUM
CSG & SX - TUBING						FORMATION	DATUM
8 5/8" 387' 140							
4 1/2" 4400' 350							
LOGS EL GR RA IND HC A							
						30 4400'	TD 4368'

IP San Andres Perfs 40-41-4340' Perfs: "Prod 181 BOPD + 24 BW.
 Pot. Based on 12 hr test at 100' TD + 1. BW thru 32/64" chk.,
 TP 100#, Gravity 25.

Distribution limited and publication prohibited by subscribers' agreement.
 Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT.	BSL Drilg. Co.	PROP. DEPTH	4500'	TYPE	
DATE					

F.R. 9-15-66; Opt's Elev. 43.4' M
 PD 4500' - SA
 Contractor - BSL Drilg. Co.
 10-10-66 TD 4400', WOC.
 10-17-66 TD 4400', PFD 4368', swbg.
 Perf @ 4214', 4221', 4228', 4241', 4248',
 4283', 4308', 4316', 4313', 4321', 4334',
 4338', 4344' w/1 SPB
 Acid (4214-4344') 5000 gals.
 Swbd 28 BAW, 17 ELO + 26 PFD in 10 1/2 hrs.
 10-24-66 TD 4400', PFD 4368', WOC PERFS.
 LOG TOPS: Top Salt 1000', Base Salt 2023',
 Yates 2307', Queen 2400', Graving 3100',
 San Andres 3480'.