

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYCOPY TO D. C. G.
SUBMIT IN 2
(Other, instruct
verse side)CATE
on reForm approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-064650

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

9. WELL NO.

WOLF Federal

10. FIELD AND POOL, OR WILDCAT

CHAVERO San Andres

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

18-7-34 NMPM

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

PAN AMERICAN PETROLEUM CORPORATION

3. ADDRESS OF OPERATOR

Box 68, Hobbs, New Mexico

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)

At surface

660' FSL x 2/50.9' FEL Sec. 18 (Unit O, SW 1/4 SE 1/4)

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GK, etc.)

4332' R. V. B.

COUNTY OR PARISH

18. STATE

R. V. B.

N. M.

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT ON:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

NOTE: If well is directionally drilled, give subsurface locations and measured and true vertical depths for all layers and zones pertinent to this work.)

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

NOTE: If well is directionally drilled, give subsurface locations and measured and true vertical depths for all layers and zones pertinent to this work.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent data, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all layers and zones pertinent to this work.)

TD-4340, On 10-1-66, 4 1/2" OD 9 5/8" J-55 casing was set at 4340' w/ 500 sq 12% Gel + 500 sq meat. Tested casing w/ 2300 psi for 30 minutes. Test O. K.

Perforated intervals 4064-66, 78-74, 80-83, 85-86, 89-90, 92-93, 94-95, 4120-22, 26-29, 46-49, 55-57, 62-63, 68-90, 70-72, 77-79, 82-84, 86-88, 92-93, 95-97, 4238-42, 45-49, 52-54, 55-57, 61-63, 65-67 w/ 2SPF. Acidized w/ 2000 gal. Frac w/ 30,000 gal oil, 40,500# sand. 3000# sand. Evaluated.

On PT, pumped 51 BO x 2 BW in 24 hours.

TD-4340' TRAY 4064, San Andres

PBD-4301 Comp 10-19-66

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Area Supt

DATE

10-20-66

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

0-4- USGS-14
1- NSW
1- SUSP
1- RRY

*See Instructions on Reverse Side