

COUNTY	ROOSEVELT		FIELD	Chaveroo	STATE	NM
OPR	MIDWEST OIL CORPORATION				MAP	
	2 Morgan-Federal Tract 3					
	Sec. 22, T-7-S, R-33-E				CO-ORD	
	1980' FSL, 660' FEL of Sec.				MX 10648	
	Spd 10-7-66		CLASS		E	
	Cmp 11-1-66		FORMATION	DATUM	FORMATION	DATUM
CSG & SX - TUBING						
8 5/8" 355' 300						
4 1/2" 4500' 975						
LOGS EL GR RA IND HC A						
			TD 4500', PBD 4284'			

IP San Andres Perfs 4135-4224' Flwd 355 BOPD + 46 BW. Pot.
Based on 3½ hr test of 52 BO + 7 BW thru 1/2" chk., TP 150#,
CP 500#, GOR 1290.

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT.	PROP DEPTH	4500'	TYPE
DATE			

F.R. 10-20-66
PD 4500' - SA

10-24-66 TD 4500', prep to perf.
Perf @ 4299', 4305', 4320', 4328', 4339',
4345', 4353', 4366', 4376' W/1 SPI
Acid (4299-4376') 1500 gals.
Frac (4299-4376') 16,000 gals oil + 16,000# sd.
Swbd 2-3 BFPH (90% LO, 10% AW)
Acid (4299-4376') 5000 gals.
Swbd 3-4 BFPH (60% LO, 40% AW) (4299-4376')

10-31-66 TD 4500', PBD 4284', flwg load.
Set GIBP @ 4284'
Perf @ 4135', 4175', 4191', 4194', 4196',
4198', 4204', 4210', 4216', 4222', 4224'
W/1 SPI
Att. Frac (4135-4224') 170 BO & Sanded Out.

10-31-66

Cont.

Perf @ 4135', 4175', 4191', 4194', 4196',
4198', 4204', 4210', 4216', 4222', 4224'

W/1 SPI

Acid (4135-4224') 3000 gals.

Frac (4135-4224') 50,000 gals oil +
50,000# sd.

Flwd 260 BLO/24 hrs thru 32/64" ch., TP
75#, CP 430# (4135-4224')

11-7-66

TD 4500', PBD 4284', WO Potential.

Flwd 52 BO + 15% wtr in 3½ hrs thru 1/2"
chk., TP 150#, CP 500#, GOR 1290.

11-14-66

TD 4500', PBD 4284', COMPLETE.

LOG TOPS: Yates 2440', San Andres 3628',
Slaughter 4023'.