

COUNTY	ROOSEVELT		FIELD	Wildcat		STATE	NM	
OPR	PAN AMERICAN PETROLEUM CORP.					MAP		
	2 Brown, J. B. Jr.							
	Sec. 6. T-7-S, R-34-E					CO-ORD		
	330' FSL, 660' FEL of Sec.					MX 10651		
	Spd 10-21-66					CLASS		
	Cmp 11-15-66					FORMATION	DATUM	FORMATION
CSG & SX - TUBING								
8 5/8" 415' 300								
4 1/2" 4210' 800								
LOGS EL GR RA IND HC A								
						TD 4210', PBD 4168'		
IP San Andres Perfs 4083-4167' Flwd 20 BOPD + 70 BW. Pot. Based on 24 hr test thru 23/64" chk., TP 120#, CP 400#, Gravity 26., GOR 13,700.								
Distribution limited and publication prohibited by subscribers' agreement. Reproduction rights reserved by Williams & Lee Scouting Service, Inc.								
CONT.	Cactus Drlg. Co.					PROP DEPTH	4500'	TYPE
DATE								

F.R. 10-20-66; Opr's Elev. 4338' KB
 PD 4500' - SA
 Contractor - Cactus
 10-17-66 Drlg. 3772'.
 10-24-66 TD 4210', MO Rotary
 Cored 4024-75', rec 51' anhy dolo., bldg
 oil from PPP & vert fracs.
 Cored 4075-4125', rec 50' being:
 23' dolo., bldg oil & wtr;
 6' dns dolo., w/NS;
 21' anhy.
 Cored 4126-76', rec 50' being:
 12' anhy;
 30' anhy dolo., fracs., PP to vuggy poro.,
 bldg oil, gas & wtr;
 8' dns lm., w/NS.

10-31-66 TD 4210', PBD 4168', swbg load.
Perf @ 4083', 4084', 4086', 4093', 4145',
4150', 4152', 4153', 4155', 4160', 4161',
4163', 4166', 4167' W/1 SPI
Acid (4083-4167') 2000 gals.
Frac (4083-4167') 48,000 gals gelled brine
+ 72,000# sd.
Swbd 525 BLW/21 hrs.
11-7-66 TD 4210', PBD 4168', Tstg.
Flwd 17 BO + 51 BLW/24 hrs thru 25/64"
chk., TP 175#. (180 BLW)
11-14-66 TD 4210', PBD 4168', Tstg.
Flwd 65 BO + 77 BLW/72 hrs thru 30/64" chk.,
TP 120#, CP 430#
11-21-66 TD 4210', PBD 4168', COMPLETE.
LOG TOPS: Yates 2115', Queen 2805', San Andres
3265'.